

BBBBBBBBBBBBBB	AAAAAAA	CCCCCCCCCCCC	KKK	KKK	UUU	PPPPPPP			
BBBBBBBBBBBBBB	AAAAAAA	CCCCCCCCCCCC	KKK	KKK	UUU	PPPPPPP			
BBBBBBBBBBBBBB	AAAAAAA	CCCCCCCCCCCC	KKK	KKK	UUU	PPPPPPP			
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	PPP	PPP
BBBBBBBBBBBBBB	AAA	AAA	CCC	KKKKKKKK	UUU	UUU	PPPPPPP		
BBBBBBBBBBBBBB	AAA	AAA	CCC	KKKKKKKK	UUU	UUU	PPPPPPP		
BBBBBBBBBBBBBB	AAA	AAA	CCC	KKKKKKKK	UUU	UUU	PPPPPPP		
BBB	BBB	AAAAAAAAAAAAAA	CCC	KKK	KKK	UUU	UUU	PPP	
BBB	BBB	AAAAAAAAAAAAAA	CCC	KKK	KKK	UUU	UUU	PPP	
BBB	BBB	AAAAAAAAAAAAAA	CCC	KKK	KKK	UUU	UUU	PPP	
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	UUU	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	UUU	PPP
BBB	BBB	AAA	AAA	CCC	KKK	KKK	UUU	UUU	PPP
BBBBBBBBBBBBBB	AAA	AAA	CCCCCCCCCCCC	KKK	KKK	UUUUUUUUUUUUUUU	PPP		
BBBBBBBBBBBBBB	AAA	AAA	CCCCCCCCCCCC	KKK	KKK	UUUUUUUUUUUUUUU	PPP		
BBBBBBBBBBBBBB	AAA	AAA	CCCCCCCCCCCC	KKK	KKK	UUUUUUUUUUUUUUU	PPP		

FILEID**BACKDEF

B 15

BBBBBBBB	AAAAAA	CCCCCCC	KK	KK	DDDDDDDD	EEEEEEEEE	FFFFFFFFF
BBBBBBBB	AAAAAA	CCCCCCC	KK	KK	DDDDDDDD	EEEEEEEEE	FFFFFFFFF
BB BB AA AA CC			KK	KK	DD DD DD	EE EE EE	FF FF FF
BB BB AA AA CC			KK	KK	DD DD DD	EE EE EE	FF FF FF
BB BB AA AA CC			KK	KK	DD DD DD	EE EE EE	FF FF FF
BB BB AA AA CC			KK	KK	DD DD DD	EE EE EE	FF FF FF
BBBBBBBB	AA AA CC		KKKKKK	DD	DD	EEEEEEEEE	FFFFFFFFF
BBBBBBBB	AA AA CC		KKKKKK	DD	DD	EEEEEEEEE	FFFFFFFFF
BB BB AAAAAAAA CC			KK KK	DD DD	DD	EE EE	FF FF
BB BB AAAAAAAA CC			KK KK	DD DD	DD	EE EE	FF FF
BB BB AA AA CC			KK KK	DD DD	DD	EE EE	FF FF
BB BB AA AA CC			KK KK	DD DD	DD	EE EE	FF FF
BBBBBBBB	AA AA CCCCCC		KK KK	DD DDDDDDD	EE	FFFF
BBBBBBBB	AA AA CCCCCC		KK KK	DD DDDDDDD	EE	FFFF

SSSSSSSS	DDDDDDDD	LL
SSSSSSSS	DDDDDDDD	LL
SS	DD DD	LL
SSSSSS	DD DD	LL
SSSSSS	DD DD	LL
SS	DD DD	LL
SSSSSSSS	DDDDDDDD	LLLLLLLL
SSSSSSSS	DDDDDDDD	LLLLLLLL

```
{ BACKDEF.SDL - BACKUP Media Structure Definitions
{ Version: 'V04-000'
{ ****
{*
{* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
{* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
{* ALL RIGHTS RESERVED.
{*
{* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
{* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
{* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
{* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
{* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
{* TRANSFERRED.
{*
{* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
{* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
{* CORPORATION.
{*
{* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
{* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
{*
{*
{****

{++
{ FACILITY: VMS BACKUP Utility
{ ABSTRACT:
{ This file contains the structure definitions for the BACKUP
media format.
{ ENVIRONMENT:
{ VAX/VMS operating system.

{--
{ AUTHOR: Andrew C. Goldstein, CREATION DATE: 27-Aug-1980 15:40
{ MODIFIED BY:
{ V03-010 LY0510 Larry Yetto 19-JUL-1984 08:47
Increase size of DEVTYPE field in physical volume attribute
record from 1 to 4
{ V03-009 LY0508 Larry Yetto 12-JUL-1984 10:13
Increase journal directory name length to be equal to MAXRSS.
MAXRSS was raised to 255 from 252 so we must follow.
{ V03-008 LY0505 Larry Yetto 11-JUL-1984 15:36
```

Correct spelling of BRH\$V_NONSEQENTIAL

V03-007 ACG0433 Andrew C. Goldstein, 9-Jul-1984 18:37
Add per block error flags to BACKUP save set format;
general SDL cleanup

V03-006 LY0489 Larry Yetto 21-MAY-1984 16:11
Increase size of journal directory name entry to
allow long directory names.

V03-005 LY0462 Larry Yetto 1-FEB-1984 10:33
Add support for journal file structure level 2

V03-004 ACG0364 Andrew C. Goldstein, 10-Oct-1983 15:51
Add BACKUP format definitions for HSC backup

V03-003 JEP0003 J. Eric Pollack, 23-Apr-1983 10:35
Add support for encrypted savesets.

V03-002 ACG0332 Andrew C. Goldstein, 26-Apr-1983 19:15
Add highwater mark and journal flags file attributes

V03-001 LMP0044 L. Mark Pilant, 21-Oct-1982 14:00
Add support for saving and restoring ACL's.

V02-007 MLJ0081 Martin L. Jack, 26-Feb-1982 15:02
Add RETAINMIN and RETAINMAX attributes for new home block
fields.

V02-006 MLJ0075 Martin L. Jack, 28-Jan-1982 19:56
Add VERLIMIT and DIR_VERLIM attributes for version limit
handling.

V02-005 MLJ0062 Martin L. Jack, 3-Dec-1981 12:13
Add DIR_STATUS attribute to support /INCREMENTAL.

V02-004 MLJ0036 Martin L. Jack, 28-Aug-1981 17:14
Implement parent directory attributes.

V02-003 MLJ0023 Martin L. Jack, 23-Apr-1981 11:28
Implement placement attribute.

V02-002 MLJ0020 Martin L. Jack, 20-Apr-1981 21:42
Implement /JOURNAL qualifier.

V02-001 MLJ0010 Martin L. Jack, 25-Mar-1981 13:43
Add subfields to block header FID and DID. Add INDEXLBN,
BOOTVBN, BOOTBLOCK attributes for image restore. Add NUM_ATRS
symbol. Change maximum length of BACKVER attribute.

{**}

```
{
{
{ BBH - BACKUP block header. This structure prefixes each physical
{ record on the backup medium. It contains fields necessary for error
{ detection and recovery, and sufficient identification to allow the
{ block to be correctly interpreted in the absence of other information.
{
}-
```

```
module $BBHDEF;
```

```
aggregate BBHDEF structure fill prefix BBH$:
  SIZE word unsigned;                                /* size in bytes of block header
  OPSYS word unsigned;                             /* operating system ID
  SUBSYS word unsigned;                            /* subsystem ID
  APPLIC word unsigned;                           /* application ID
  NUMBER longword unsigned;                         /* block sequence number
  FILL_1 byte dimension 20 fill prefix BBHDEF tag $$; /* reserved
  constant "COMMON" equals . prefix BBH$ tag K;      /* end of common header
  constant "COMMON" equals . prefix BBH$ tag C;      /* end of common header

  STRUCLEV structure word unsigned;                /* block structure level
    STRUCVER byte unsigned;                        /* structure version number
    STRUCLEV byte unsigned;                        /* major structure level
    constant LEVEL1 equals 257 prefix BBH tag $K;   /* level 1, version 1
  end STRUCLEV;

  VOLNUM word unsigned;                           /* media volume number
  CRC longword unsigned;                          /* block CRC
  BLOCKSIZE longword unsigned;                   /* block size in bytes
  FLAGS structure longword unsigned;
    NOCRC bitfield mask;                         /* no CRC computed for block
  end FLAGS;

  SSNAME character length 32;                    /* save set name (counted ASCII)
/* *** Note: Old overlay form must be used in FID & DID due to SDL bug
/* *** that omits the field size symbol in a structured field.
  FID_OVERLAY union fill;
    FID word unsigned dimension 3;                /* current file ID
    FID_FIELDS structure fill;
      FID_NUM word unsigned;                      /* file number
      FID_SEQ word unsigned;                      /* file sequence number
    FID_RVN OVERLAY union fill;
      FID_RVN word unsigned;                     /* relative volume number
      FID_RVN_FIELDS structure fill;
        FID_RVN byte unsigned;                  /* alternate format RVN
        FID_NMX byte unsigned;                  /* alternate format file number extension
      end FID_RVN_FIELDS;
    end FID_RVN_OVERLAY;
  end FID_FIELDS;
end FID_OVERLAY;

  DID_OVERLAY union fill;
    DID word unsigned dimension 3;                /* current directory ID
    DID_FIELDS structure fill;
      DID_NUM word unsigned;                    /* file number
      DID_SEQ word unsigned;                   /* file sequence number
```

```
DID_RVN_OVERLAY union fill;
    DID_RVN word unsigned;                      /* relative volume number
    DID_RVN_FIELDS structure fill;
        DID_RVN byte unsigned;                  /* alternate format RVN
        DID_NMX byte unsigned;                  /* alternate format file number extension
    end DID_RVN_FIELDS;
end DID_RVN_OVERLAY;
end DID_FIELDS;
end DID OVERLAY;
FILENAME character length 128;                   /* current file name
RTYPE byte unsigned;                          /* record type of current file
RATTRIB byte unsigned;                        /* record attributes of current file
RSIZE word unsigned;                         /* record size of current file
BKTSIZE byte unsigned;                       /* bucket size of current file
VFCSIZE byte unsigned;                        /* VFC area size of current file
MAXREC word unsigned;                         /* maximum record size of current file
FILESIZE longword unsigned;                  /* allocation of current file
RESERVED2 character length 22;                /* reserved
CHECKSUM word unsigned;                      /* header checksum
constant "LENGTH" equals . prefix BBH$ tag K; /* length of block header
constant "LENGTH" equals . prefix BBH$ tag C; /* length of block header

end BBBDEF;
end_module $BBHDEF;
```

```
module $BRHDEF;
/*+
/*
/* BRH - backup record header. This structure prefixes each record
/* within a data block. It identifies the type and use of the record.
/*
/*-
aggregate BRHDEF structure fill prefix BRHS;
    RSIZE word unsigned;                                /* record size in bytes
    RTYPE word unsigned;                               /* record type
    constant(
        NULL;                                         /* null record
        , SUMMARY;                                     /* BACKUP summary record
        , VOLUME;                                     /* volume summary record
        , FILE;                                       /* file attribute record
        , VBN;                                         /* file virtual block record
        , PHYSVOL;                                    /* physical volume attribute record
        , LBN;                                         /* physical volume logical block record
        , FID;                                         /* file ID record
        , FILE_EXT;                                    /* file attribute extension record
        , LBN_576;                                     /* 576 byte LBN record
    ) equals 0 increment 1 prefix BRH tag $K;

FLAGS structure longword unsigned;
    BADDATA bitfield mask;                           /* record flags
    DIRECTORY bitfield mask;                         /* data error occurred in record
    NONSEQUENTIAL bitfield mask;                     /* record belongs to a directory file
    BLOCKERRS bitfield mask;                         /* data record is not in LBN / VBN sequence
end FLAGS;
"ADDRESS" longword unsigned;                        /* per block error mask present
BLOCKFLAGS word unsigned;                          /* address of data (e.g., VBN or LBN)
RESERVED word unsigned;                           /* per block error mask
constant "LENGTH" equals . prefix BRHS tag K;      /* reserved
constant "LENGTH" equals . prefix BRHS tag C;

end BRHDEF;
end_module $BRHDEF;
```

```
module $BSADEF;  
/*+  
/*  
/* BACKUP attribute codes. These attributes appear in various records  
/* in a save set.  
/*  
/*-  
  
/*  
/* Definition for file ID record  
/* (Structure level definition shared with other attribute records)  
/*  
  
aggregate BSADEF structure fill prefix BSA$;  
    STRUCLEV word unsigned;                      /* save set structure level  
    FID_NUM word unsigned;                       /* NUM word of file ID  
    FID_RVN structure word unsigned;             /* RVN word of file ID  
        FID_RVN byte unsigned;                    /* alternate format RVN word  
        FID_NMX byte unsigned;                    /* alternate format RVN word  
    end FID_RVN;  
    FID_COUNT word unsigned;                     /* count of SEQ words following  
    FID_SEQ word unsigned;                       /* SEQ word of file ID, repeated  
                                                /* BSA$W_FID_COUNT times  
  
/*  
/* Attribute entry header  
/*  
  
end BSADEF;  
  
aggregate BSADEF1 structure fill prefix BSA$;  
    SIZE word unsigned;                         /* size of attribute value  
    TYPE word unsigned;                         /* attribute code  
    constant 'LENGTH' equals . prefix BSA$ tag K; /* length of attribute descriptor  
    constant 'LENGTH' equals . prefix BSA$ tag C; /* length of attribute descriptor  
  
/*  
/* Data item within placement attribute record  
/*  
  
end BSADEF1;  
  
aggregate BSADEF2 structure fill prefix BSA$;  
    PLC_PTR word unsigned;                      /* placement pointer  
    PLC_COUNT longword unsigned;                /* count of placed blocks  
    PLC_LBN structure longword unsigned;         /* LBN of placed blocks  
        PLC_LOLBN word unsigned;  
        PLC_HILBN word unsigned;  
    end PLC_LBN;  
end BSADEF2;
```

```
/*
/* Attribute type codes
*/

/*
/* BACKUP summary record
*/

constant(
    SSNAME          /* save set name
    ,COMMAND        /* command line
    ,COMMENT         /* user comment
    ,USERNAME        /* name of user who wrote the set
    ,USERUIC         /* UIC of user
    ,DATE            /* date backup was done
    ,OPSYST          /* operating system
    ,SYSVER          /* operating system version
    ,NODENAME        /* operating system node name
    ,SIR             /* CPU system ID register
    ,DRIVEID         /* ID of drive writing backup
    ,BACKVER         /* version number of BACKUP
    ,BLOCKSIZE       /* block size of save set
    ,XORSIZE         /* size of each XOR group
    ,BUFFERS          /* number of buffers
    ,VOLSETNAM       /* volume set name
    ,NVOLS           /* number of volumes in set
    ,BACKSIZE         /* total file space in save set
    ,BACKFILES        /* total number of files in save set

/*
/* Volume summary record
*/

    ,VOLSTRUCT        /* volume structure level
    ,VOLNAME          /* volume label
    ,OWNERNAME        /* volume owner name
    ,FORMAT           /* volume file format name
    ,RVN              /* relative volume number
    ,VOLOWNER         /* volume owner UIC
    ,PROTECT          /* volume protection mask
    ,FILEPROT         /* volume default file protection
    ,RECPROT          /* volume default record protection
    ,VOLCHAR          /* volume characteristics bits
    ,VOLDATE          /* volume creation date
    ,WINDOW           /* default file window size
    ,LRU_LIM          /* default directory LRU limit
    ,EXTEND           /* default file extend size
    ,CLUSTER          /* storage map cluster factor
    ,RESFILES         /* number of reserved files
    ,VOLSIZE          /* original volume size in blocks
    ,TOTSIZE          /* total file space in volume set
    ,TOTFILES         /* total number of files in volume set
    ,MAXFILES         /* maximum number of files allowed
    ,MAXFILENUM       /* highest file number
    ,SERIALNUM        /* pack serial number
```

```
/*
/* File attribute record
*/

. FILENAME           /* file name
. STRUCLEV          /* file structure level
. FID                /* file ID
. BACKLINK           /* directory ID back link
. FILESIZE           /* file size in blocks
. UIC                /* file owner UIC
. FPRO               /* file protection mask
. RPRO               /* record protection mask
. ACLEVEL            /* access level
. UCHAR              /* file characteristics
. RECATTR            /* record attributes area
. REVISION           /* revision number
. CREDATE            /* creation date
. REVDATE            /* revision date
. EXPDATE            /* expiration date
. BAKDATE            /* backup date

/*
/* Physical volume attribute record
*/

. SECTORS            /* sectors per track
. TRACKS             /* tracks per cylinder
. CYLINDERS          /* cylinders per volume
. MAXBLOCK           /* number of logical blocks per volume
. DEVTYPE            /* device type
. SERIAL              /* serial number
. DEVNAM              /* device name
. LABEL              /* label
. BADBLOCK           /* bad block descriptor, a sequence of
                        /* pairs of longwords where the first
                        /* is an LBN, the second is a count

/*
/* Additions
*/

. INDEXLBN           /* (VS) Index file bitmap starting LBN
. BOOTBLOCK           /* (VS) Boot block image
. BOOTVBN             /* (FA) VBN within file for boot block
. PLACEMENT           /* (FA) Placement data
. DIR_UIC             /* (FA) UIC of directory
. DIR_FPRO            /* (FA) Protection of directory
. DIR_STATUS          /* (FA) Status of directory
. DIR_VERLIM          /* (FA) Version limit of directory
. VERLIMIT            /* (FA) File version limit
. RETAINMIN           /* (VS) Minimum file retention period
. RETAINMAX           /* (VS) Maximum file retention period
. ACLSEGMENT          /* (FA) ACL segment for the file
. HIGHWATER           /* (FA) Highwater mark
. JNL_FLAGS            /* (FA) Journal control flags
```

```
, CRYPTKEY           /* (BS) File encryption attribute
, LBNSIZE            /* (PS) Disk block size in bytes
; NUM_ATRS          /* number of attribute codes
; equals 1 increment 1 prefix BSA tag $K;

/*
/* Placement data type codes
/*
constant(
    PLC_FID           /* file ID
, PLC_COUNT          /* count of unplaced blocks
, PLC_PLACE          /* placement pointer, count of placed blocks
, PLC_PLLBN          /* placement pointer, count, LBN of placed blocks
) equals 1 increment 1 prefix BSA tag $K;
```

```
/*
/* Lengths of above attributes
*/

/*
/* BACKUP summary record
*/

constant SSNAME      equals 32  prefix BSA tag $$; /* save set name
constant COMMAND     equals 512 prefix BSA tag $$; /* command line
constant COMMENT      equals 512 prefix BSA tag $$; /* user comment
constant USERNAME    equals 32  prefix BSA tag $$; /* name of user who wrote the set
constant USERUIC      equals 4   prefix BSA tag $$; /* UIC of user
constant DATE        equals 8   prefix BSA tag $$; /* date backup was done
constant OPSYS        equals 2   prefix BSA tag $$; /* operating system
constant SYSVER       equals 4   prefix BSA tag $$; /* operating system version
constant NODENAME    equals 12  prefix BSA tag $$; /* operating system node name
constant SIR          equals 4   prefix BSA tag $$; /* CPU system ID register
constant DRIVEID     equals 16  prefix BSA tag $$; /* ID of drive writing backup
constant BACKVER      equals 32  prefix BSA tag $$; /* version number of BACKUP
constant BLOCKSIZE    equals 4   prefix BSA tag $$; /* block size of save set
constant XORSIZE      equals 2   prefix BSA tag $$; /* size of each XOR group
constant BUFFERS       equals 2   prefix BSA tag $$; /* number of buffers
constant VOLSETNAM    equals 12  prefix BSA tag $$; /* volume set name
constant NVOLS         equals 2   prefix BSA tag $$; /* number of volumes in set
constant BACKSIZE      equals 8   prefix BSA tag $$; /* total file space in save set
constant BACKFILES     equals 4   prefix BSA tag $$; /* total number of files in save set

/*
/* Volume summary record
*/

constant VOLSTRUCT    equals 2   prefix BSA tag $$; /* volume structure level
constant VOLNAME       equals 12  prefix BSA tag $$; /* volume label
constant OWNERNAME     equals 12  prefix BSA tag $$; /* volume owner name
constant FORMAT        equals 12  prefix BSA tag $$; /* volume file format name
constant RVN           equals 2   prefix BSA tag $$; /* relative volume number
constant VOLOWNER      equals 4   prefix BSA tag $$; /* volume owner UIC
constant PROTECT       equals 2   prefix BSA tag $$; /* volume protection mask
constant FILEPROT      equals 2   prefix BSA tag $$; /* volume default file protection
constant RECPROT       equals 2   prefix BSA tag $$; /* volume default record protection
constant VOLCHAR       equals 2   prefix BSA tag $$; /* volume characteristics bits
constant VOLDATE       equals 8   prefix BSA tag $$; /* volume creation date
constant WINDOW        equals 1   prefix BSA tag $$; /* default file window size
constant LRU LIM        equals 1   prefix BSA tag $$; /* default directory LRU limit
constant EXTEND        equals 2   prefix BSA tag $$; /* default file extend size
constant CLUSTER       equals 2   prefix BSA tag $$; /* storage map cluster factor
constant RESFILES      equals 2   prefix BSA tag $$; /* number of reserved files
constant VOLSIZE        equals 4   prefix BSA tag $$; /* original volume size in blocks
constant TOTSIZE        equals 8   prefix BSA tag $$; /* total file space in volume
constant TOTFILES       equals 4   prefix BSA tag $$; /* total number of files in volume
constant MAXFILES       equals 4   prefix BSA tag $$; /* maximum number of files allowed
constant MAXFILNUM      equals 4   prefix BSA tag $$; /* highest file number
constant SERIALNUM      equals 4   prefix BSA tag $$; /* pack serial number
```

```
/*
/* File attribute record

constant FILENAME equals 128 prefix BSA tag $$; /* file name
constant STRUCLEV equals 2 prefix BSA tag $$; /* file structure level
constant FID equals 6 prefix BSA tag $$; /* file ID
constant BACKLINK equals 6 prefix BSA tag $$; /* directory ID back link
constant FILESIZE equals 4 prefix BSA tag $$; /* file size in blocks
constant UIC equals 4 prefix BSA tag $$; /* file owner UIC
constant FPRO equals 2 prefix BSA tag $$; /* file protection mask
constant RPRO equals 2 prefix BSA tag $$; /* record protection mask
constant ACLEVEL equals 1 prefix BSA tag $$; /* access level
constant UCHAR equals 4 prefix BSA tag $$; /* file characteristics
constant RECATTR equals 32 prefix BSA tag $$; /* record attributes area
constant REVISION equals 2 prefix BSA tag $$; /* revision number
constant CREATE equals 8 prefix BSA tag $$; /* creation date
constant REVDATE equals 8 prefix BSA tag $$; /* revision date
constant EXPDATE equals 8 prefix BSA tag $$; /* expiration date
constant BAKDATE equals 8 prefix BSA tag $$; /* backup date

/*
/* Physical volume attribute record
/*

constant SECTORS equals 1 prefix BSA tag $$; /* sectors per track
constant TRACKS equals 1 prefix BSA tag $$; /* tracks per cylinder
constant CYLINDERS equals 2 prefix BSA tag $$; /* cylinders per volume
constant MAXBLOCK equals 4 prefix BSA tag $$; /* number of logical blocks per volume
constant DEVTYPE equals 4 prefix BSA tag $$; /* device type
constant SERIAL equals 4 prefix BSA tag $$; /* serial number
constant DEVNAM equals 64 prefix BSA tag $$; /* device name
constant LABEL equals 12 prefix BSA tag $$; /* label
constant BADBLOCK equals 8 prefix BSA tag $$; /* bad block descriptor (one pair)

/*
/* Additions
/*

constant INDEXLBN equals 4 prefix BSA tag $$; /* (VS) Index file bitmap starting LBN
constant BOOTBLOCK equals 512 prefix BSA tag $$; /* (VS) Boot block image
constant BOOTVBN equals 4 prefix BSA tag $$; /* (FA) VBN within file for boot block
constant PLACEMENT equals 2048 prefix BSA tag $$; /* (FA) Placement data
constant DIR_UIC equals 4 prefix BSA tag $$; /* (FA) UIC of directory
constant DIR_FPRO equals 2 prefix BSA tag $$; /* (FA) Protection of directory
constant DIR_STATUS equals 1 prefix BSA tag $$; /* (FA) Status of directory
constant DIR_VERLIM equals 2 prefix BSA tag $$; /* (FA) Version limit of directory
constant VERLIMIT equals 2 prefix BSA tag $$; /* (FA) File version limit
constant RETAINMIN equals 8 prefix BSA tag $$; /* (VS) Minimum file retention period
constant RETAINMAX equals 8 prefix BSA tag $$; /* (VS) Maximum file retention period
constant ACLSEGMENT equals 380 prefix BSA tag $$; /* (FA) ACL segment for the file
constant HIGHWATER equals 4 prefix BSA tag $$; /* (FA) Highwater mark
constant JNL_FLAGS equals 2 prefix BSA tag $$; /* (FA) Journal control flags
constant CRYPTDATKEY equals 24 prefix BSA tag $$; /* (BS) Saveset encryption key
constant LBNSIZE equals 2 prefix BSA tag $$; /* (PS) Disk block size in bytes
```

```
/*
/* Placement data type codes
*/

constant PLC_FID equals 6 prefix BSA tag $$; /* file ID
constant PLC_COUNT equals 4 prefix BSA tag $$; /* count of unplaced blocks
constant PLC_PLACE equals 6 prefix BSA tag $$; /* placement pointer, count of placed blocks
constant PLC_PLLBN equals 10 prefix BSA tag $$; /* placement pointer, count, LBN of placed blocks

{
{ Fields of a CRYPTDATKEY attribute record
{

aggregate BSADEF3 structure fill prefix BSA$;
    CRYPTYP byte unsigned;           /* Byte code describing saveset encr alg
    constant(
        CRYP_DESCBC                /* Code for DES Cypher Block Chaining
        ,CRYP_DESECB                /* Code for DES Electronic Code Book.
    ) equals 1 increment 1 prefix BSA$ tag K;
    CRYPRES0 character length 3 fill; /* Unused
    CRYPKEY quadword unsigned;      /* DES key used to encrypt saveset
    CRYPIV quadword unsigned;       /* DES initialize vector prototype
    CRYPCKSM longword unsigned;    /* Checksum for attribute record
end BSADEF3;

end_module $BSADEF;
```

```
module $BJLDEF;
/**+
/* BACKUP journal file.
*/
/*-
```

```
aggregate BJLDEF structure fill prefix BJL$;
    SIZE byte unsigned;                      /* record length (XOR format)
    TYPE byte unsigned;                      /* record type
    constant(
        STRUCLEV                         /* structure level
        , SSNAME                           /* save set name
        , VOLUME                           /* volume identification
        , DIRECTORY                         /* directory name
        , FILE                             /* file name
    ) equals 0 increment 1 prefix BJL tag $K;

    DATA byte unsigned;                     /* beginning of data portion of record

/*
/* Following definitions are all relative to data portion of record.
*/
/* Structure level record.
*/
/*-
```

```
end BJLDEF;

aggregate BJLDEF1 structure fill prefix BJL$;
    STRUCLEV structure word unsigned;          /* structure level
        STRUCVER byte unsigned;                /* structure version number
        STRUCLEV byte unsigned;                /* major structure level
        constant LEVEL1 equals 257  prefix BJL tag $K; /* level 1, version 1
        constant LEVEL2 equals 258  prefix BJL tag $K; /* level 1, version 2
    end STRUCLEV;
    constant STRUC_LEN equals . prefix BJL$ tag K; /* length of record
    constant STRUC_LEN equals . prefix BJL$ tag C; /* length of record

/*
/* Save set name record.
*/
/*-
```

```
end BJLDEF1;

aggregate BJLDEF2 structure fill prefix BJL$;
    CREDATE quadword unsigned;                 /* creation date and time
    SSNAME character length 32;                /* save set name (variable length)
    constant SSNAME_LEN equals . prefix BJL$ tag K; /* maximum length of record
    constant SSNAME_LEN equals . prefix BJL$ tag C; /* maximum length of record

/*
/* Volume identification record.
*/
/*-
```

```
end BJLDEF2;

aggregate BJLDEF3 structure fill prefix BJL$;
  VOLNAME character length 12;          /* volume label
  VOLNUMBER word unsigned;             /* volume sequence number
  constant VOLUME_LEN equals . prefix BJL$ tag K; /* length of record
  constant VOLUME_LEN equals . prefix BJL$ tag C; /* length of record

/*
/* Directory record.
*/

end BJLDEF3;

aggregate BJLDEF4 structure fill prefix BJL$;
  DIRNAME character length 255;        /* directory name (variable length)
  constant DIR_LEN equals . prefix BJL$ tag K; /* maximum length of record
  constant DIR_LEN equals . prefix BJL$ tag C; /* maximum length of record
                                              /* stored in XOR format

/*
/* File record.
*/

end BJLDEF4;

/* The following masks define flag bits. The structure is being defined
/* in this way because the flags do not have a set position in the record
/* defined by BJLDEF5 but simply follow directly after the file name.
/* By defining the structures in this manner there is a full longword
/* reserved but is not position dependant
aggregate FLAG_BITS structure fill prefix BJL$ ;
  HEADONLY bitfield mask ;           /* NOBACKUP was set when file was saved
end FLAG_BITS ;

aggregate BJLDEF5 structure fill prefix BJL$;
  FILENAME character length 128;       /* file name (variable length)
  FLAGS longword unsigned fill;      /* flags
  constant FILE_LEN equals . prefix BJL$ tag K; /* maximum length of record
  constant FILE_LEN equals . prefix BJL$ tag C; /* maximum length of record

end BJLDEF5;
end_module $BJLDEF;
```

0009 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

BACKDEF
SD

COMMON
REQ

BACKUP

BACKUP
MAP

STABACOP
MAP

STABACOP
MAP

RMSREPORT
15

RMSSTATS
LTS

STABACOP
MAP