CLD

```
HH        HH  EEEEEEEEEE  LL           PPPPPPPP
HH        HH  EEEEEEEEEE  LL           PPPPPPPP
HH        HH  EE          LL           PP      PP
HH        HH  EE          LL           PP      PP
HH        HH  EE          LL           PP      PP
HHHHHHHHHH  EEEEEEE       LL           PPPPPPPP
HHHHHHHHHH  EEEEEEE       LL           PPPPPPPP
HH        HH  EE          LL           PP
HH        HH  EE          LL           PP
HH        HH  EE          LL           PP         ....
HH        HH  EE          LL           PP         ....
HH        HH  EEEEEEEEEE  LLLLLLLLLL   PP         :::
HH        HH  EEEEEEEEEE  LLLLLLLLLL   PP         :::


    CCCCCCC   LL           DDDDDDD
    CCCCCCC   LL           DDDDDDD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
CC            LL           DD      DD
    CCCCCCC   LLLLLLLLLL   DDDDDDD
    CCCCCCC   LLLLLLLLLL   DDDDDDD
```

```
  Version:        'V04-000'

       V03-002 MCN0173        Maria del C. Nasr        25-Jun-1984
                 Make /OUTPUT qualifier default to SYS$OUTPUT

       V03-001 PCG0001        Peter George             11-Apr-1984
                 Add DISALLOW statements.


DEFINE TYPE scope_keywords
        KEYWORD              ALL,default
        KEYWORD              NONE
        KEYWORD              PROCESS
        KEYWORD              GROUP
        KEYWORD              SYSTEM

DEFINE VERB HELP
        IMAGE VMSHELP
        PARAMETER            P1,label=keywords,
                             value(type=$rest_of_line)
        QUALIFIER            PROMPT,default
        QUALIFIER            PAGE,default
        QUALIFIER            INSTRUCTIONS,default
        QUALIFIER            OUTPUT,default
                             value(type=$file,default="SYS$OUTPUT")
        QUALIFIER            LIBRARY,default,
                             value(type=$infile,default="HELPLIB")
        QUALIFIER            LIBLIST,default
        QUALIFIER            USERLIBRARY,default,negatable,
                             value(type=scope_keywords,list)
        DISALLOW             (ALL and NONE)
        DISALLOW             (ALL or NONE) and (PROCESS or GROUP or SYSTEM)
```

BACKUP CLD

DCLTABLES CLD

DISMOUNT CLD

ENCRYPT CLD

REPLY CLD

CLD

CREATE CLD

MCRINT CLD

SET CLD

DCLTABLES MAP

DEF CLD

DMO CLD

LIBRARIAN CLD

PASCAL CLD

RUN CLD

ACC CLD

BAD CLD

DCLINT CLD

DELETE CLD

DUMP CLD

EXCHANGE CLD

MCRTABLES CLD

PATCH CLD

CHECKSUM CLD

ANALYZE CLD

EDIT CLD

FORTRAN CLD

LINK CLD

MESSAGE CLD

PHONE CLD

CLISYM1 CLD

MCRSET CLD

RUNOFF CLD

PSECTS R32

DIFF CLD

MONITOR CLD

RECOVER CLD

MCRTABLES MAP

CONVERT CLD

HELP CLD

MACRO CLD

DIRECTORY CLD

SDL CLD

JNLUSR MAR

COPY CLD

EDT CLD

INIT CLD

MOUNT CLD

RENAME CLD

MAIL CLD

SEARCH CLD