

Instruction Manual

MON 86 — V 1.5A

8086 Monitor

For Use with the SCP 300 CPU Support Board

REV. 1.5A



Seattle Computer Products, Inc.

1114 Industry Drive, Seattle, WA. 98188
(206) 575-1830

CONTENTS

Getting Started	3
Parameters	4
Commands	4
Boot	4
Dump	5
Enter	6
Fill	6
Go	7
Input	7
Move	8
Output	8
Register	8
Search	9
Trace	10
8086 Monitor Assembly Listing	11

Getting Started

Connect an RS-232 terminal to the cable coming from J1 of the CPU support card. The terminal should be set for full duplex at one of the following rates: 19200, 9600, 1200, 300, 150, or 110 baud. The software-selected baud rate feature of the CPU Support card is used to automatically determine the baud rate of the terminal. By hitting the carriage return no more than four times, the sign-on message should appear. If it does not, reset the computer and try again. If it still does not sign on, check all connections carefully.

If Sense Switch 0 is a one (position 1 of S2 is closed), then the monitor will NOT sign on after baud rate selection but instead will automatically boot the disk. This is equivalent to the Boot command with no parameters.

Directly below the sign-on message there will be a greater-than symbol, ">". This is the Monitor prompt, and indicates that the Monitor is ready to accept a command. The input buffer allows commands of up to 80 characters in length. While typing the command line, <backspace> and <rubout> or <delete> may be used back up to correct a mistake, while "@" cancels the line and re-issues the prompt. Typing <carriage return> either causes the command to be executed or an error to be reported. Most errors are syntax errors, and an arrow followed by the word "Error" will appear under the first bad character. If an error occurs, no part of the command is executed (except during boot or flag replacement - see Boot and Register commands).

Monitor commands are available to display, alter and search memory; to do inputs and outputs; to boot the disk; and to aid in debugging 8086 programs. The debugging commands allow the user to execute a program in a controlled manner, observing its behavior. This controlled execution may be done either by single-stepping or through execution with breakpoints.

Single-stepping is done with the Monitor's Trace command. By using 8086 hardware trace mode, a single instruction can be executed, and the resulting effects on the registers or memory displayed. Even ROM may be traced, and every instruction is traced correctly (unlike 8080 or Z80 debuggers).

Execution with breakpoints (Go command) allows the user to quickly execute previously tested program portions but stops program execution if a breakpoint is reached. Breakpoints require more care than single-stepping since they can only be used in RAM at the address of the first byte of an 8086 opcode.

Both methods of "controlled execution" allow the user to modify or examine CPU registers. A "register save area" is maintained in memory: just before execution, all registers are set with values from this area; and when control is returned to the monitor, all registers are saved back in this area. The Register command allows this area to be displayed or modified.

Execution of any command may be aborted by typing Control-C. Typing Control-S during output will cause the display to pause so it may be read before scrolling away; any key (except Control-C) may be typed to continue.

If a user program is executing as a result of a Boot or Go command and interrupts are enabled, then the console may interrupt the program and return control to the Monitor. Typing any key will cause the interrupt, save program status, and print a register dump; except that Control-C will inhibit the register dump. Note that complete program status is always saved, and execution may be continued with a Go or Trace command.

The Monitor requires .5K of memory at address zero. Specifically, interrupt vectors are kept at locations 4-7, 0CH-0FH, and 64H-67H, while scratch pad ram, input buffer, and stack use less than 256 bytes beginning at 100H. User programs must not modify these locations if the Monitor is to be used for debugging.

Parameters

All commands of the Monitor accept one or more parameters on the line following the command letter. These parameters MAY be separated from each other and the command letter by spaces or commas, but one of these delimiters is REQUIRED only to separate consecutive hex values. Most parameters are one of the following types:

<BYTE>, <HEX4>, <ADDRESS> - A hexadecimal number with no more than 2, 4, or 5 digits, respectively. Thus, <BYTE> becomes an 8-bit value, <HEX4> a 16-bit value, and <ADDRESS> a 20-bit value. If too many digits are entered or a non-hex character is typed, the error arrow will point to the mistake. Hex A-F must be in upper case.

<RANGE> - A <RANGE> is either <ADDRESS> <ADDRESS> or <ADDRESS> L <HEX4>. The first form specifies the first and last addresses affected by the command. The second form specifies a starting address and a length. For either form, the maximum length (first address - last address + 1) cannot exceed 10000H, and this limit may be as low as OFFF1H due to limitations of working within a segment. (Specifically, [starting address modulo 16] + length must be <= 10000H.) An "RG Error" results if the length is too large. To specify a length of 10000H with only four digits, use a length of zero. Note that the "L" in this form must be upper case.

<LIST> - This is always the last parameter on a line and may extend to the end of the input buffer. It is actually a series of one or more parameters, each of which is either a <BYTE> or a <STRING>.

A <STRING> is any number of characters (except control characters) enclosed by either single ('') or double ("") quotes. Since the opening and closing quotes must be the same, the other type may appear in the string freely. If the same quote as opened the string needs to appear within it, it must be given as two adjacent quotes. The ASCII values of the characters in the string are used as a list of bytes.

Commands

A command is executed by typing the first letter of its name (upper case only) followed by any parameters. If the first letter on the line is not recognized as a command, the error arrow will point to it. Commands are listed below in alphabetical order, with the forms of all parameters shown.

B

B <ADDRESS> . . . <ADDRESS>

Boot - Loads the first sector of track 0 of the disk into memory starting at 200H. Up to ten 5-digit addresses may be specified; too many will cause a "BP Error". After the sector is loaded, breakpoints will be set at these locations. Then all registers will be set from the register save area, except that the Code Segment will be set to zero, and the Instruction Pointer will be set to 200H - thus a jump will be made to 200H. The user stack pointer MUST be valid for this command to work. See Go command for more information.

This command works in three steps. First, the disk sector is loaded. Next, the Code Segment and Instruction Pointer are set in the register save area. Finally, a Go command is executed. The result is that an error in a breakpoint address will not be found until AFTER the sector is loaded and the register save area changed. Thus it is not necessary to use another Boot command to correct the error; a Go command with the corrected breakpoints will do.

The example below shows how Boot can help test an experimental 8086 program. The program to be tested fits into one 128-byte sector and has been placed on track 0, sector 1 of a disk. The program is loaded with the Boot command but execution does not begin because a breakpoint is set at 200H, the first byte of loaded program. Before testing, the program is moved to 400H, just above the interrupt table, and CS and IP are adjusted.

SCF 8086 Monitor 1.4

>B200

```
AX=0000 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000
DS=0040 ES=0040 SS=0040 CS=0000 IP=0200 NV UP EI PL NZ NA PO NC
> M 200 L80 400
>RCS
CS 0000
:t40
>R IP
IP 0200
:t0
>R
AX=0000 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000
DS=0040 ES=0040 SS=0040 CS=0040 IP=0000 NV UP EI PL NZ NA PO NC
>
```

D <ADDRESS>

D <RANGE>

Dump - Displays memory contents in hex and ASCII. If only a starting address is specified, 80H bytes are dumped; otherwise the specified range is displayed. To help pinpoint addresses, each line (except possibly the first) begins on a 16-byte boundary, and each 8-byte boundary is marked with a "-". Non-printing characters are shown as a "." in the ASCII dump.

```
>D400 L29
00400 FF FB FF FF F7 7F FF FF-FF FE 7F FF FF FF FF FF FF FF FF .C...W...+^...+...
00410 DD FB DF FF CF FF FE DF-FF FF 7F FB FB FD FF F7 J-C...+0.^...+...CC...W
00420 BF FF BF FF BF BF 6F FF-FF ?..?..??.o...
>
>D445 463
00445 FF DF 7F-F9 FF 7E FF FE FF FF FF +....W+^+^+...
00450 FF FF FF FF FF FF DF-FF D7 FF FF FF FF FF FF FF +....W+...+...
00460 9F FF FA FF +...Z+
>
>D80
00080 FF DF FF FF DF FF FF FF-F5 FF FF FD FF FS FF 7F +....+...+...U...+...D...+...
00090 CE FF FF FB FF FB FF FF-ZF FF FE FA FD FA FF FB N...C...C...+...^zD...z...C
000A0 FF DF DF +....+....+....+....+...
000B0 FF FF FB BF FF FF SF EF-FF FF FA FF FF DF F7 FD +...C?...+...O...+...Z...+...W...
000C0 FF FF FF FF FF FF FF-ZF FF FE FF FE E6 FF FF +....+....+....+....+...
000D0 FF DF FF FF DC FB ZF-FE FF FF FF FF DB ED FF +....+...N...^...+....+...E...
000E0 FF FF FF FB FF FF FF-FF FF FF FF FF FF SF FF +....C...+....+....+...
000F0 DF F7 FF DE FF FF BD-BF BF F9 FB DF FF DF DF ...W+^...+...=??yC...+...
```

E <ADDRESS> <LIST>
E <ADDRESS>

Enter - In the first form, the list of bytes is entered at the specified address, with the command being executed and completed upon hitting <carriage return>. If an error occurs, NO locations are changed.

The second form puts the Monitor into "Enter Mode", starting at the specified address. After hitting <carriage return>, the address and its current contents will be displayed. The user now has several options:

1) Replace the displayed value with a new value. Simply type in the new value in hex, using <backspace> or <delete> to correct mistakes. If an illegal hex digit is typed or more than two digits are typed, the bell will sound and the character will not be echoed. After entering the new value, type either <space>, "-", or <carriage return>, as defined below.

2) Type <space> to display and possibly replace the next memory location. Every 8-byte boundary will start a new line with the current address.

3) Type "-" to backup to the preceding memory location. This will always start a new line with the address. The "-" will not be echoed.

4) Type <carriage return> to terminate the command.

```
>E500 24,9,A 'Test',0
>D 500 L10
00500 24 09 0A 54 65 73 74 00-00 20 00 00 00 40 01 00    $..Test.. ...@..
>
>E508
00508 00,
00507 00,
00506 74.    00.49
00508 00.4E   20.47  00.0    00.0    00.0    40.0    01.0    00.
00510 60.    01.    01.76  00.
>D500 513
00500 24 09 0A 54 65 73 74 49-4E 47 00 00 00 00 00 00    $..TestING.....
00510 60 01 76 00
`vv.
```

F <RANGE> <LIST>

Fill - The specified range is filled with the values in the list. If the list is larger than the range, not all values will be used; if the range is larger, the list will be repeated as many times as necessary to fill it. All memory in <RANGE> must be valid for this command to work properly. If bad or non-existent memory is encountered, the error will be propagated into all succeeding locations.

```
>F400 L28 "Help" A D
>D400 L30
00400 48 65 6C 70 0A 0D 48 65-6C 70 0A 0D 48 65 6C 70    Help..Help..Help
00410 0A 0D 48 65 6C 70 0A 0D-48 65 6C 70 0A 0D 48 65    ..Help..Help..He
00420 6C 70 0A 0D 48 65 6C 70-FF 7F FF FF FF F7 FF    lpe..Help.....w+
>
```

G

G <ADDRESS> . . . <ADDRESS>

Go - Sets all registers from the register save area. Since this includes the Code Segment and Instruction Pointer, this implies a jump to the program under test.

This command allows setting up ten breakpoints. Attempting to set more than ten will cause a "BP Error". Breakpoints may be set only at an address containing the first byte of an 8086 opcode. A breakpoint is set by placing an interrupt opcode (0CCH) at the specified address. When that opcode is executed, all registers are saved and displayed, and all breakpoints locations are restored to their original value. If control is not returned to the Monitor by a breakpoint or interrupt, the breakpoints will not be cleared.

The user stack pointer must be valid and have 6 bytes available for this command to work. The jump to the user program is made with an IRET instruction with the user stack pointer set and user Flags, Code Segment register, and Instruction Pointer on the user stack. Thus if the user stack is not valid, the system will "crash".

The program below is an infinite loop of 16 INC AX instructions followed by a jump to its start. First breakpoints are used to execute a few instructions. Then a Go without breakpoints allows continuous, full-speed execution which is terminated by an interrupt from the keyboard - in this case, typing the space bar.

```
>F400 L10 40  
>E410 EB EE  
>D400 L12  
00400 40 40 40 40 40 40 40-40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40  
00410 EB EE  
>  
>G410  
  
AX=0010 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0010 NV UP EI PL NZ AC PO NC  
>G400 412  
  
AX=0010 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0000 NV UP EI PL NZ AC PO NC  
>G  
  
AX=4590 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0000 NV UP EI PL NZ AC PE NC  
>
```

I <HEX4>

Input - Inputs a byte from the specified port and displays it. A 16-bit port address is allowed.

M <RANGE> <ADDRESS>

Move - Moves the block of memory specified by <RANGE> to <ADDRESS>. Overlapping moves are always performed without loss of data, i.e., data is moved before it is overwritten. To do this, all moves from higher addresses to lower ones are done front-to-back, while moves from lower addresses to higher ones are done back-to-front.

```
>M400 L10 420
>D400 42F
00400 54 45 53 54 49 4E 47 FF-F7 FF FF F6 FF FF FE FF TESTING.w...v...^
00410 FF FF FE FF ..^.....^.....^
00420 54 45 53 54 49 4E 47 FF-F7 FF FF F6 FF FF FE FF FF TESTING.w...v...^
>
>M404 40F 405
>D400 L10
00400 54 45 53 54 49 49 4E 47-FF F7 FF FF F6 FF FF FE FE TESTING.w...v...^
>
>M405 410 404
>D400L10
00400 54 45 53 54 49 4E 47 FF-F7 FF FF F6 FF FF FE FF TESTING.w...v...^
>
```

O <HEX4> <BYTE>

Output - <BYTE> is sent to the specified output port. A 16-bit port address is allowed.

R

R <REGISTER NAME>

Register - with no parameters, this command dumps the register save area.

Giving a register name as a parameter allows that register to be displayed and modified. The register name may be AX, BX, CX, DX, SP, BP, SI, DI, DS, ES, SS, CS, IP, PC, or F (upper case only); anything else will result in an "BR Error". IP and PC both refer to the Instruction Pointer and F refers to the Flag register. For all except the Flag register, the current 16-bit value will be printed in hex, then a colon will appear as a prompt for the replacement value. Typing <carriage return> leaves the register unchanged; otherwise type a <HEX4> to replace.

The Flag register uses a system of two-letter mnemonics for each flag, as shown below:

<u>FLAG</u>	<u>CLEAR</u>	<u>SET</u>
Overflow	NV No Overflow	OV Overflow
Direction	UP Up (Incrementing)	DN Down (Decrementing)
Interrupt	DI Disabled Interrupts	EI Enabled Interrupts
Sign	PL Plus	NG Negative
Zero	NZ Not Zero	ZR Zero
Auxillary Carry	NA No Auxillary Carry	AC Auxillary Carry
Parity	PO Parity Odd	PE Parity Even
Carry	NC No Carry	CY Carry

Whenever the Flag register is displayed, all flags are displayed in this order. When the F register is specified with the R command, the flags are displayed and then the Monitor waits for any replacements to be made. Any number of two-letter flag codes may be typed, and only those flags entered will be modified. If a flag has more than one code in the list, a "DF Error" (Double Flag) will result. If any code is not recognized, a "BF Error" (Bad Flag) will occur. In either case, those flags up to the error have been changed, and those after the error have not.

After reset, all registers are set to zero except the segment registers, which are set to 40H, and the Stack Pointer, which is set to 0C00H. Flags are all cleared except for interrupts. Execution on a Trace or Go command would thus begin at 400H, which is the first location after the interrupt table.

```
>R
AX=0000 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000
DS=0040 ES=0040 SS=0040 CS=0040 IP=0000 NV UP EI PL NZ AC PE NC
>R AX
AX 0000
:106
>RCS
CS 0040
:
>RF
NV UP EI PL NZ AC PE NC -ZR DN
>R
AX=0106 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000
DS=0040 ES=0040 SS=0040 CS=0040 IP=0000 NV DN EI PL ZR AC PE NC
>
```

S <RANGE> <LIST>

Search - The range is searched for a byte or string of bytes specified by <LIST>. For each occurrence the first address of the match is displayed.

```
>S400 L8000 'Help'
00400
00406
0040C
00412
00418
0041E
00424
>D400 L28
00400 48 65 6C 70 0A 0D 48 65-6C 70 0A 0D 48 65 6C 70    Help..Help..Help
00410 0A 0D 48 65 6C 70 0A 0D-48 65 6C 70 0A 0D 48 65    ..Help..Help..He
00420 6C 70 0A 0D 48 65 6C 70                                lP..Help
>
```

T

T <HEX4>

Trace - The number of instructions specified (default 1) are traced. After each instruction, the complete contents of the registers and flags are displayed. (For the meaning of the flag symbols, see Register command.) Since this command uses the hardware trace mode of the 8086, even ROM may be traced.

```
>R  
AX=0106 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0000 NV DN EI PL ZR AC PE NC  
>T  
AX=0107 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0001 NV DN EI PL NZ NA PO NC  
>T4  
AX=0108 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0002 NV DN EI PL NZ NA PO NC  
>T4  
AX=0109 BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0003 NV DN EI PL NZ NA PE NC  
AX=010A BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0004 NV DN EI PL NZ NA PE NC  
AX=010B BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0005 NV DN EI PL NZ NA PO NC  
AX=010C BX=0000 CX=0000 DX=0000 SP=0C00 BP=0000 SI=0000 DI=0000  
DS=0040 ES=0040 SS=0040 CS=0040 IP=0006 NV DN EI PL NZ NA PE NC  
>
```

8086 Monitor Assembly Listing

```
0000 ; Seattle Computer Products 8086 Monitor version 1.5 4/24/80
0000 ; by Tim Paterson
0000 ; This software is not copyrighted.
0000
0000
0000 ;To select a disk boot, set one of the following equates
0000 ;to 1, the rest to 0.
0000
0000 CROMEMCO4FDC: EQU 0 ;1 for 4FDC, 0 for others
0000 NORTHSTARSD: EQU 0 ;North Star single density?
0000 TARBELL: EQU 1 ;Tarbell (single or double)?
0000 OTHER: EQU 0 ;User-defined disk
0000
0000 PUTBASE:EQU 100H
0000 LOAD: EQU 200H
0000 ORG 7FOH
07F0 PUT PUTBASE+7FOH
07F0 EA 00 00 80 FF JMP 0,OFF80H ;Power-on jump to monitor
07F5
07F5 ;Baud Rate Table. The 9513 divides 2MHz by these values.
07F5 ;They are for 9600, 1200, 300, 150, 110 baud
07F5
07F5 OD 00 68 00 A0 01 BAUD: DW 13,104,416,832,1144
        40 03 78 04
07FF
07FF ORG 100H ;RAM area base address
0100
0100 ;System Equates
0100
0100 BASE: EQU OFOH ;CPU Support base port address
0100 STAT: EQU BASE+7 ;UART status port
0100 DATA: EQU BASE+6 ;UART data port
0100 DAV: EQU 2 ;UART data available bit
0100 TBMT: EQU 1 ;UART transmitter ready bit
0100 BUflen: EQU 80 ;Maximum length of line input buffer
0100 BPMax: EQU 10 ;Maximum number of breakpoints
0100 BPLEN: EQU BPMax+BPMax ;Length of breakpoint table
0100 REGTABLEN:EQU 14 ;Number of registers
0100 SEGDIF: EQU 800H ;-OFF800H (ROM address)
0100 PROMPT: EQU ">" ;RAM area.
0100 CAN: EQU "@"
0100
0100 BRKCNT: DS 2 ;Number of breakpoints
0102 TCOUNT: DS 2 ;Number of steps to trace
0104 BPTAB: DS BPLEN ;Breakpoint table
0118 LINEBUF:DS BUFLEN+1 ;Line input buffer
0169 ALIGN
016A DS 50 ;Working stack area
019C STACK:
019C
019C ;Register save area
019C
019C AXSAVE: DS 2
019E BXSAVE: DS 2
01A0 CXSAVE: DS 2
01A2 DXSAVE: DS 2
01A4 SPSAVE: DS 2
01A6 BPSAVE: DS 2
01A8 SISAVE: DS 2
01AA DISAVE: DS 2
01AC DSSAVE: DS 2
01AE ESSAVE: DS 2
01B0 RSTACK: ;Stack set here so registers can be saved by pushing
01B0 SSSAVE: DS 2
01B2 CSSAVE: DS 2
01B4 IPSAVE: DS 2
```

```

01B6      FSAVE: DS      2
01B8
01B8      ;Start of Monitor code
01B8
01B8      ORG    0
0000      PUT    PUTBASE
0000
0000      ;One-time initialization
0000
0000 FC      UP
0001 33 C0      XOR    AX,AX
0003 8E D0      MOV    SS,AX
0005 8E D8      MOV    DS,AX
0007 8E C0      MOV    ES,AX
0009 BF 9C 01      MOV    DI,AXSAVE
000C B9 0E 00      MOV    CX,14
000F F3      REP
0010 AB      STOW
0011 80 0E B7 01 02      OR    B,[FSAVE+1],2      ;Set register images to zero
0016 B1 04      MOV    CL,4      ;Enable interrupts
0018 B0 40      MOV    AL,40H
001A BF AC 01      MOV    DI,DSSAVE
001D F3      REP
001E AB      STOW
001F C6 06 A5 01 0C      MOV    B,[SPSAVE+1],0CH      ;Set segment reg. images to 40H
0024 BC 9C 01      MOV    SP,STACK      ;Set user stack to 400H+0C00H
0027          ;Prepare 9513
0027 B0 17      MOV    AL,17H
0029 E6 F5      OUT   BASE+5      ;Select Master Mode register
002B B0 F3      MOV    AL,0F3H
002D E6 F4      OUT   BASE+4      ;Low byte of Master Mode
002F B8 84 05      MOV    AX,584H      ;Output 84H to BASE+4
0032 E7 F4      OUTW  BASE+4      ;and 05H to BASE+5
0034          ;Master Mode now set to 84F3H:
0034          ;Scaler set to BCD division
0034          ;Enable data pointer increment
0034          ;8-bit data bus
0034          ;FOUT=100Hz, dividing F5 by 4 (F5=4MHz/10000)
0034          ;Both alarm comparators disabled
0034          ;Time-of-day enabled
0034          ;Counter 5 selected
0034
0034          ;Initialize loop. Ports BASE through BASE+7 are initialized
0034          ;from table. Each table entry has number of bytes followed by
0034          ;data.
0034 BE 33 07      MOV    SI,INITTABLE      ;Initialization table
0037 BA F0 00      MOV    DX,BASE      ;DX has (variable) port no.
003A          INITPORT:
003A 2E      SEG   CS
003B AC      LODB
003C 8A C8      MOV    CL,AL
003E E3 05      JCXZ NEXTPORT      ;No init. for some ports
0040          INITBYTE:
0040 2E      SEG   CS
0041 AC      LODB
0042 EE      OUT   DX      ;Get init. data
0043 E2 FB      LOOP  INITBYTE      ;Send to port
0043          ;As many bytes as required
0045          NEXTPORT:
0045 42      INC   DX      ;Prepare for next port
0046 80 FA F8      CMP   DL,BASE+8      ;Check against limit
0049 75 EF      JNZ   INITPORT
004B
004B          ;Initialization complete except for determining baud rate.
004B          ;Both 8259As are ready to accept interrupts, the 9513 is
004B          ;providing 19.2k baud X 16 to the 8251A which is set for
004B          ;16X clock and one stop bit.
004B
004B E8 19 00      CALL  CHECKB      ;Check for correct baud rate
004E          ;CHECKB does not return if baud rate is correct

```

```

004E ;Initial baud rate (19.2k) was wrong, so run auto-baud routine
004E
004E
004E
004E
004E BE F5 07
0051 ;First set up 9513 for slower baud rates (<=9600).
0051 ;Counter 5 mode register has already been selected.
0051 B8 23 E8
0054 E7 F4
0056 ;MOV AX,0E823H ;Output 23H to BASE+4
0056 ;OUTW BASE+4 ;and 0E8H to BASE+5
0056 ;23H to BASE+4 sets lower half of Counter 5 mode register.
0056 ;Reload from Load, count down repetitively in binary,
0056 ;toggle output.
0056 ;0E8H to BASE+5 disables data pointer sequencing
0056
0056 B0 0D
0058 E6 F5
005A INITB:
005A 2E
005B AD
005C E6 F4
005E 8A C4
0060 E6 F4
0062 E8 02 00
0065 EB F3
0067
0067 E8 98 00
006A E8 95 00
006D 3C 0D
006F 74 01
0071 C3
0072
0072 ;Initialization complete, including baud rate.
0072
0072
0072 MONITOR:
0072 ; Do auto boot if sense switch 0 is on.
0072 BF 18 01
0075 C6 05 0D
0078 E4 FF
007A A8 01
007C 74 03
007E E9 F5 06
0081
0081 BE 51 07
0084 E8 8B 00
0087
0087 FC
0088 33 C0
008A 8E D8
008C 8E C0
008E BC 9C 01
0091 C7 06 64 00 BB 06
0097 8C 0E 66 00
009B B0 3E
009D E8 C8 00
00A0 E8 1E 00
00A3
00A3 ;From now and throughout command line processing, DI points
00A3 ;to next character in command line to be processed.
00A3 E8 7F 00
00A6 74 DF
00A8 8A 05
00AA
00AA 2C 42
00AC 72 10
00AE 3C 13
00B0 73 0C
00B2 47
00B3 D0 E0
00B5 98
00B6 93
    MOV SI,BAUD
    MOV AX,0E823H ;Output 23H to BASE+4
    OUTW BASE+4 ;and 0E8H to BASE+5
    ;23H to BASE+4 sets lower half of Counter 5 mode register.
    ;Reload from Load, count down repetitively in binary,
    ;toggle output.
    ;0E8H to BASE+5 disables data pointer sequencing
    MOV AL,0DH
    OUT BASE+5 ;Select Counter 5 load reg.
    SEG CS
    LODW ;Get divisor
    OUT BASE+4 ;Output low byte
    MOV AL,AH
    OUT BASE+4 ;Output high byte
    CALL CHECKB ;Check if baud rate correct.
    JP INITB ;Try next rate if not
    CHECKB:
    CALL IN ;First byte could be messed up
    CALL IN ;Get carriage return
    CMP AL,13 ;Correct?
    JZ MONITOR ;Don't return if correct
    RET ;Didn't get it yet
    ;Initialization complete, including baud rate.
    ;Do auto boot if sense switch 0 is on.
    MOV DI,LINEBUF
    MOV B,[DI],13 ;No breakpoints after boot
    IN BASE+0FH ;Sense switch port
    TEST AL,1
    JZ DOMON
    JMP BOOT
    DOMON:
    MOV SI,HEADER
    CALL PRINTMES
    COMMAND:
    ;Re-establish initial conditions
    UP
    XOR AX,AX
    MOV DS,AX
    MOV ES,AX
    MOV SP,STACK
    MOV [64H],INT ;Set UART interrupt vector
    MOV [66H],CS
    MOV AL,PROMPT
    CALL OUT
    CALL INBUF ;Get command line
    ;From now and throughout command line processing, DI points
    ;to next character in command line to be processed.
    CALL SCANB ;Scan off leading blanks
    JZ COMMAND ;Null command?
    MOV AL,[DI] ;AL=first non-blank character
    ;Prepare command letter for table lookup
    SUB AL,"B" ;Low end range check
    JC ERR1
    CMP AL,"T"+1-"B" ;Upper end range check
    JNC ERR1
    INC DI
    SHL AL ;Times two
    CBW ;Now a 16-bit quantity
    XCHG BX,AX ;In BX we can address with it

```

00B7 2E	SEG	CS		
00B8 FF 97 7D 01	CALL	[BX+COMTAB]	;Execute command	
00BC EB C9	JP	COMMAND	;Get next command	
00BE E9 A8 02	ERR1:	JMP	ERROR	
00C1				
00C1			;Get input line	
00C1				
00C1 BF 18 01	INBUF:	MOV	DI,LINEBUF	;Next empty buffer location
00C4 33 C9		XOR	CX,CX	;Character count
00C6	GETCH:	CALL	IN	;Get input character
00C6 E8 39 00		CMP	AL,20H	;Check for control characters
00C9 3C 20		JC	CONTROL	
00CB 72 1B		CMP	AL,7FH	;RUBOUT is a backspace
00CD 3C 7F		JZ	BACKSP	
00CF 74 0E		CALL	OUT	;Echo character
00D1 E8 94 00		CMP	AL,CAN	;Cancel line?
00D4 3C 40		JZ	KILL	
00D6 74 25		STOB		;Put in input buffer
00D8 AA		INC	CX	;Bump character count
00D9 41		CMP	CX,BUFLEN	;Buffer full?
00DA 83 F9 50		JBE	GETCH	;Drop in to backspace if full
00DD 76 E7	BACKSP:	JCXZ	GETCH	;Can't backspace over nothing
00DF E3 E5		DEC	DI	;Drop pointer
00E1 4F		DEC	CX	;and character count
00E2 49		CALL	BACKUP	;Send physical backspace
00E3 E8 29 00		JP	GETCH	;Get next char.
00E6 EB DE	CONTROL:	CMP	AL,8	;Check for backspace
00E8 3C 08		JZ	BACKSP	
00EA 74 F3		CMP	AL,13	;Check for carriage return
00EC 3C 0D		JNZ	GETCH	;Ignore all other control char.
00EE 75 D6		STOB		;Put the car. ret. in buffer
00F0 AA		MOV	DI,LINEBUF	;Set up DI for command processing
00F1 BF 18 01				
00F4				
00F4				;Output CR/LF sequence
00F4				
00F4	CRLF:	MOV	AL,13	
00F4 B0 0D		CALL	OUT	
00F6 E8 6F 00		MOV	AL,10	
00F9 B0 0A		JP	OUT	
00FB EB 6B				
00FD				
00FD				;Cancel input line
00FD				
00FD	KILL:	CALL	CRLF	
00FD E8 F4 FF		JP	COMMAND	
0100 EB 85				
0102				
0102				;Character input routine
0102				
0102 FA	IN:	DI		;Poll, don't interrupt
0103 E4 F7		INB	STAT	
0105 A8 02		TEST	AL,DAV	
0107 74 F9		JZ	IN	;Loop until ready
0109 E4 F6		INB	DATA	
010B 24 7F		AND	AL,7FH	;Only 7 bits
010D FB		EI		;Interrupts OK now
010E C3		RET		
010F				
010F				;Physical backspace - blank, backspace, blank
010F				
010F	BACKUP:	MOV	SI,BACMES	
010F BE 73 07				
0112				;Print ASCII message. Last char has bit 7 set
0112				

```

0112 PRINTMES:
0112 2E SEG CS
0113 AC LODB ;Get char to print
0114 E8 51 00 CALL OUT
0117 D0 E0 SHL AL ;High bit set?
0119 73 F7 JNC PRINTMES
011B C3 RET
011C
011C ;Scan for parameters of a command
011C
011C SCANP:
011C E8 06 00 CALL SCANB ;Get first non-blank
011F 82 3D 2C CMP B,[DI],"," ;One comma between params OK
0122 75 0A JNE EOLCHK ;If not comma, we found param
0124 47 INC DI ;Skip over comma
0125
0125 ;Scan command line for next non-blank character
0125
0125 SCANB:
0125 B0 20 MOV AL," "
0127 51 PUSH CX ;Don't disturb CX
0128 B1 FF MOV CL,-1 ;but scan as many as necessary
012A F3 REPE
012B AE SCAB
012C 4F DEC DI ;Back up to first non-blank
012D 59 POP CX
012E EOLCHK:
012E 82 3D 0D CMP B,[DI],13
0131 C3 RET
0132
0132 ;Print the 5-digit hex address of SI and DS
0132
0132 OUTSI:
0132 8C DA 11011010 MOV DX,DS ;Put DS where we can work with it
0134 B4 00 MOV AH,0 ;Will become high bits of DS
0136 E8 78 00 CALL SHIFT4 ;Shift DS four bits
0139 03 D6 ADD DX,SI ;Compute absolute address
013B EB 09 JP OUTADD ;Finish below
013D
013D ;Print 5-digit hex address of DI and ES
013D ;Same as OUTSI above
013D
013D OUTDI:
013D 8C C2 MOV DX,ES
013F B4 00 MOV AH,0
0141 E8 6D 00 CALL SHIFT4
0144 03 D7 ADD DX,DI
0146 ;Finish OUTSI here too
0146 OUTADD:
0146 82 D4 00 ADC AH,0 ;Add in carry to high bits
0149 E8 12 00 CALL HIDIG ;Output hex value in AH
014C
014C ;Print out 16-bit value in DX in hex
014C
014C OUT16:
014C 8A C6 MOV AL,DH ;High-order byte first
014E E8 02 00 CALL HEX
0151 8A C2 MOV AL,DL ;Then low-order byte
0153
0153 ;Output byte in AL as two hex digits
0153
0153 HEX:
0153 8A E0 MOV AH,AL ;Save for second digit
0155 ;Shift high digit into low 4 bits
0155 51 PUSH CX
0156 B1 04 MOV CL,4
0158 D2 E8 SHR AL,CL
015A 59 POP CX
015B
015B E8 02 00 CALL DIGIT ;Output first digit

```

```

015E HIDIG:           MOV     AL,AH      ;Now do digit saved in AH
015E 8A C4
0160 DIGIT:           AND     AL,0FH     ;Mask to 4 bits
0160 24 0F
0162 ;Trick 6-byte hex conversion works on 8086 too.
0162 04 90
0164 27
0165 14 40
0167 27
0168
0168 ;Console output of character in AL
0168
0168 OUT:             PUSH    AX        ;Character to output on stack
0168
0168 OUT1:            INB    STAT
0169 E4 F7
016B 24 01
016D 74 FA
016F 58
0170 E6 F6
0172 C3
0173
0173 ;Output one space
0173
0173 BLANK:           MOV     AL," "
0173 B0 20
0175 EB F1
0177
0177 ;Output the number of blanks in CX
0177
0177 TAB:              CALL    BLANK
0177 E8 F9 FF
017A E2 FB
017C C3
017D
017D ;Command Table. Command letter indexes into table to get
017D ;address of command. PERR prints error for no such command.
017D
017D COMTAB:
017D 76 07
017F 68 03
0181 0D 02
0183 88 03
0185 97 02
0187 6A 06
0189 68 03
018B 4C 06
018D 68 03
018F 68 03
0191 68 03
0193 6A 02
0195 68 03
0197 59 06
0199 68 03
019B 68 03
019D 2F 04
019F BA 02
01A1 6A 05
01A3
01A3 ;Given 20-bit address in AH:DX, breaks it down to a segment
01A3 ;number in AX and a displacement in DX. Displacement is
01A3 ;always zero except for least significant 4 bits.
01A3
01A3 GETSEG:
01A3 8A C2
01A5 24 0F
01A7 E8 07 00
01AA 8A D0
01AC 8A C6
01AE 32 F6
          MOV     AL,DL
          AND     AL,0FH      ;AL has least significant 4 bits
          CALL   SHIFT4      ;4-bit left shift of AH:DX
          MOV     DL,AL      ;Restore lowest 4 bits
          MOV     AL,DH      ;Low byte of segment number
          XOR     DH,DH      ;Zero high byte of displacement

```

```

01B0 C3           RET
01B1
01B1 ;Shift AH:DX left 4 bits
01B1
01B1 SHIFT4:
01B1 D1 E2       SHL    DX
01B3 D0 D4       RCL    AH      ;1
01B5 D1 E2       SHL    DX
01B7 D0 D4       RCL    AH      ;2
01B9 D1 E2       SHL    DX
01BB D0 D4       RCL    AH      ;3
01BD D1 E2       SHL    DX
01BF D0 D4       RCL    AH      ;4
01C1 C3           RET2:   RET
01C2
01C2 ;RANGE - Looks for parameters defining an address range.
01C2 ;The first parameter is a hex number of 5 or less digits
01C2 ;which specifies the starting address. The second parameter
01C2 ;may specify the ending address, or it may be preceded by
01C2 ;"L" and specify a length (4 digits max), or it may be
01C2 ;omitted and a length of 128 bytes is assumed. Returns with
01C2 ;segment no. in AX and displacement (0-F) in DX.
01C2
01C2 RANGE:
01C2 B9 05 00     MOV    CX,5      ;5 digits max
01C5 E8 22 01     CALL   GETHEX   ;Get hex number
01C8 50           PUSH   AX        ;Save high 4 bits
01C9 52           PUSH   DX        ;Save low 16 bits
01CA E8 4F FF     CALL   SCANP   ;Get to next parameter
01CD 82 3D 4C     CMP    B,[DI],"L" ;Length indicator?
01D0 74 1C           JE    GETLEN
01D2 BA 80 00     MOV    DX,128   ;Default length
01D5 E8 30 01     CALL   HEXIN    ;Second parameter present?
01D8 72 1B           JC    RNGRET   ;If not, use default
01DA B9 05 00     MOV    CX,5      ;5 hex digits
01DD E8 0A 01     CALL   GETHEX   ;Get ending address
01E0 8B CA           MOV   CX,DX   ;Low 16 bits of ending addr.
01E2 5A           POP    DX        ;Low 16 bits of starting addr.
01E3 5B           POP    BX        ;BH=hi 4 bits of start addr.
01E4 2B CA           SUB   CX,DX   ;Compute range
01E6 1A E7           SBB   AH,BH   ;Finish 20-bit subtract
01E8 75 1D           JNZ   RNGERR   ;Range must be less than 64K
01EA 93           XCHG   AX,BX   ;AH=starting, BH=ending hi 4 bits
01EB 41           INC    CX        ;Range must include ending location
01EC EB 0B           JP    RNGCHK   ;Finish range testing and return
01EE
01EE 47           INC    DI        ;Skip over "L" to length
01EF B9 04 00     MOV    CX,4      ;Length may have 4 digits
01F2 E8 F5 00     CALL   GETHEX   ;Get the range
01F5
01F5 8B CA           MOV   CX,DX   ;Length
01F7 5A           POP    DX        ;Low 16 bits of starting addr.
01F8 58           POP    AX        ;AH=hi 4 bits of starting addr.
01F9
01F9 ;RNGCHK verifies that the range lies entirely within one segment.
01F9 ;CX=0 means count=10000H. Range is within one segment only if
01F9 ;adding the low 4 bits of the starting address to the count is
01F9 ;<=10000H, because segments can start only on 16-byte boundaries.
01F9
01F9 RNGCHK:
01F9 8B DA           MOV   BX,DX   ;Low 16 bits of start addr.
01FB 81 E3 0F 00     AND   BX,0FH  ;Low 4 bits of starting addr.
01FF E3 04           JCXZ  MAXRNG  ;If count=10000H then BX must be 0
0201 03 D9           ADD   BX,CX   ;Must be <=10000H
0203 73 9E           JNC   GETSEG  ;OK if strictly <
0205
0205 MAXRNG:
0205 ;If here because of JCXZ MAXRNG, we are testing if low 4 bits
0205 ;(in BX) are zero. If we dropped straight in, we are testing
0205 ;for BX+CX=10000H (=0). Either way, zero flag set means
0205 ;within range.

```

0205 74 9C	JZ	GETSEG
0207	RNGERR:	
0207 B8 52 47	MOV	AX, 4700H+"R" ;RG ERROR
020A E9 1F 03	JMP	ERR
020D	;Dump an area of memory in both hex and ASCII	
020D	DUMP:	
020D E8 B2 FF	CALL	RANGE ;Get range to dump
0210 50	PUSH	AX ;Save segment
0211 E8 4E 01	CALL	GETEOL ;Check for errors
0214 1F	POP	DS ;Set segment
0215 8B F2	MOV	SI,DX ;SI has displacement in segment
0217	ROW:	
0217 E8 18 FF	CALL	OUTSI ;Print address at start of line
021A 56	PUSH	SI ;Save address for ASCII dump
021B	BYTE:	
021B E8 55 FF	CALL	BLANK ;Space between bytes
021E	BYTE1:	
021E AC	LODB	;Get byte to dump
021F E8 31 FF	CALL	HEX ;and display it
0222 5A	POP	DX ;DX has start addr. for ASCII dump
0223 49	DEC	CX ;Drop loop count
0224 74 17	JZ	ASCII ;If through do ASCII dump
0226 8B C6	MOV	AX, SI
0228 A8 0F	TEST	AL, OFH ;On 16-byte boundary?
022A 74 0C	JZ	ENDROW
022C 52	PUSH	DX ;Didn't need ASCII addr. yet
022D A8 07	TEST	AL, 7 ;On 8-byte boundary?
022F 75 EA	JNZ	BYTE
0231 B0 2D	MOV	AL, "-" ;Mark every 8 bytes
0233 E8 32 FF	CALL	OUT
0236 EB E6	JP	BYTE1
0238	ENDROW:	
0238 E8 02 00	CALL	ASCII ;Show it in ASCII
023B EB DA	JP	ROW ;Loop until count is zero
023D	ASCII:	
023D 51	PUSH	CX ;Save byte count
023E 8B C6	MOV	AX, SI ;Current dump address
0240 8B F2	MOV	SI, DX ;ASCII dump address
0242 2B C2	SUB	AX, DX ;AX=length of ASCII dump
0244	;Compute tab length. ASCII dump always appears on right side	
0244	;screen regardless of how many bytes were dumped. Figure 3	
0244	;characters for each byte dumped and subtract from 51, which	
0244	;allows a minimum of 3 blanks after the last byte dumped.	
0244 8B D8	MOV	BX, AX
0246 D1 E0	SHL	AX ;Length times 2
0248 03 C3	ADD	AX, BX ;Length times 3
024A B9 33 00	MOV	CX, 51
024D 2B C8	SUB	CX, AX ;Amount to tab in CX
024F E8 25 FF	CALL	TAB
0252 8B CB	MOV	CX, BX ;ASCII dump length back in CX
0254	ASCDMP:	
0254 AC	LODB	;Get ASCII byte to dump
0255 24 7F	AND	AL, 7FH ;ASCII uses 7 bits
0257 3C 7F	CMP	AL, 7FH ;Don't try to print RUBOUT
0259 74 04	JZ	NOPRT
025B 3C 20	CMP	AL, " " ;Check for control characters
025D 73 02	JNC	PRIN
025F	NOPRT:	
025F B0 2E	MOV	AL, "." ;If unprintable character
0261	PRIN:	
0261 E8 04 FF	CALL	OUT ;Print ASCII character
0264 E2 EE	LOOP	ASCDMP ;CX times
0266 59	POP	CX ;Restore overall dump length
0267 E9 8A FE	JMP	CRLF ;Print CR/LF and return
026A	;Block move one area of memory to another. Overlapping moves	
026A	;are performed correctly, i.e., so that a source byte is not	
026A	;overwritten until after it has been moved.	

026A
 026A MOVE:
 026A E8 55 FF CALL RANGE ;Get range of source area
 026D 51 PUSH CX ;Save length
 026E 50 PUSH AX ;Save segment
 026F 8B F2 MOV SI,DX ;Set source displacement
 0271 B9 05 00 MOV CX,5 ;Allow 5 digits
 0274 E8 73 00 CALL GETHEX ;in destination address
 0277 E8 E8 00 CALL GETEOL ;Check for errors
 027A E8 26 FF CALL GETSEG ;Convert dest. to seg/disp
 027D 8B FA MOV DI,DX ;Set dest. displacement
 027F 5B POP BX ;Source segment
 0280 8E DB MOV DS,BX
 0282 8E C0 MOV ES,AX ;Destination segment
 0284 59 POP CX ;Length
 0285 3B FE CMP DI,SI ;Check direction of move
 0287 1B C3 SBB AX,BX ;Extend the CMP to 32 bits
 0289 72 07 JB COPYLIST ;Move forward into lower mem.
 028B ;Otherwise, move backward. Figure end of source and destination
 028B ;areas and flip direction flag.
 028B 49 DEC CX
 028C 03 F1 ADD SI,CX ;End of source area
 028E 03 F9 ADD DI,CX ;End of destination area
 0290 FD DOWN ;Reverse direction
 0291 41 INC CX
 0292 COPYLIST:
 0292 A4 MOVB ;Do at least 1 - Range is 1-10000H not 0-FFFFH
 0293 49 DEC CX
 0294 F3 REP
 0295 A4 MOVB ;Block move
 0296 C3 RET
 0297 ;Fill an area of memory with a list values. If the list
 0297 ;is bigger than the area, don't use the whole list. If the
 0297 ;list is smaller, repeat it as many times as necessary.
 0297 FILL:
 0297 E8 28 FF CALL RANGE ;Get range to fill
 029A 51 PUSH CX ;Save length
 029B 50 PUSH AX ;Save segment number
 029C 52 PUSH DX ;Save displacement
 029D E8 B4 00 CALL LIST ;Get list of values to fill with
 02A0 5F POP DI ;Displacement in segment
 02A1 07 POP ES ;Segment
 02A2 59 POP CX ;Length
 02A3 3B D9 CMP BX,CX ;BX is length of fill list
 02A5 BE 18 01 MOV SI,LINEBUF ;List is in line buffer
 02A8 E3 02 JCXZ BIGRNG
 02AA 73 E6 JAE COPYLIST ;If list is big, copy part of it
 02AC BIGRNG:
 02AC 2B CB SUB CX,BX ;How much bigger is area than list?
 02AE 87 D9 XCHG CX,BX ;CX=length of list
 02B0 57 PUSH DI ;Save starting addr. of area
 02B1 F3 REP
 02B2 A4 MOVB ;Move list into area
 02B3 5E POP SI
 02B4 ;The list has been copied into the beginning of the
 02B4 ;specified area of memory. SI is the first address
 02B4 ;of that area, DI is the end of the copy of the list
 02B4 ;plus one, which is where the list will begin to repeat.
 02B4 ;All we need to do now is copy [SI] to [DI] until the
 02B4 ;end of the memory area is reached. This will cause the
 02B4 ;list to repeat as many times as necessary.
 02B4 8B CB MOV CX,BX ;Length of area minus list
 02B6 06 PUSH ES ;Different index register
 02B7 1F POP DS ;requires different segment reg.
 02B8 EB D8 JP COPYLIST ;Do the block move
 02BA
 02BA ;Search a specified area of memory for given list of bytes.
 02BA ;Print address of first byte of each match.

```

02BA
02BA
02BA E8 05 FF          CALL    RANGE      ;Get area to be searched
02BD 51                PUSH    CX        ;Save count
02BE 50                PUSH    AX        ;Save segment number
02BF 52                PUSH    DX        ;Save displacement
02C0 E8 91 00          CALL    LIST      ;Get search list
02C3 4B                DEC     BX        ;No. of bytes in list-1
02C4 5F                POP     DI        ;Displacement within segment
02C5 07                POP     ES        ;Segment
02C6 59                POP     CX        ;Length to be searched
02C7 2B CB              SUB     CX,BX   ; minus length of list

02C9
02C9 BE 18 01          MOV     SI,LINEBUF ;List kept in line buffer
02CC AC                LODB
02CD
02CD AE                SCAB
02CE E0 FD              LOOPNE DOSCAN   ;Search for first byte
02D0 75 C4              JNZ    RET       ;Do at least once by using LOOP
02D2 53                PUSH    BX        ;Exit if not found
02D3 87 CB              XCHG    BX,CX   ;Length of list minus 1
02D5 57                PUSH    DI        ;Will resume search here
02D6 F3                REPE
02D7 A6                CMPB
02D8 8B CB              MOV     CX,BX   ;Compare rest of string
02DA 5F                POP     DI        ;Area length back in CX
02DB 5B                POP     BX        ;Next search location
02DC 75 08              JNZ    TEST     ;Restore list length
02DE 4F                DEC     DI        ;Continue search if no match
02DF E8 5B FE              CALL   OUTDI   ;Match address
02E2 47                INC     DI        ;Print it
02E3 E8 0E FE              CALL   CRLF    ;Restore search address
02E6
02E6 E3 AE              JCXZ   RET
02E8 EB DF              JP     SCAN    ;Look for next occurrence

02EA
02EA ;Get the next parameter, which must be a hex number.
02EA ;CX is maximum number of digits the number may have.
02EA
02EA
02EA E8 2F FE              CALL   SCANP   ;Scan to next parameter
02ED
02ED 33 D2                XOR    DX,DX   ;Initialize the number
02EF 8A E6                MOV     AH,DH
02F1 E8 14 00              CALL   HEXIN   ;Get a hex digit
02F4 72 73                JC     ERROR   ;Must be one valid digit
02F6 8A D0                MOV     DL,AL   ;First 4 bits in position
02F8
02F8 47                INC     DI        ;Next char in buffer
02F9 49                DEC     CX        ;Digit count
02FA E8 0B 00              CALL   HEXIN   ;Get another hex digit?
02FD 72 97                JC     RET      ;All done if no more digits
02FF E3 68                JCXZ   ERROR   ;Too many digits?
0301 E8 AD FE              CALL   SHIFT4  ;Multiply by 16
0304 0A D0                OR     DL,AL   ;and combine new digit
0306 EB F0                JP     GETLP   ;Get more digits
0308
0308 ;Check if next character in the input buffer is a hex digit
0308 ;and convert it to binary if it is. Carry set if not.
0308
0308
0308 8A 05                MOV     AL,[DI]
030A
030A ;Check if AL has a hex digit and convert it to binary if it
030A ;is. Carry set if not.
030A
030A
030A
030A 2C 30                SUB     AL,"0"   ;Kill ASCII numeric bias
030C 72 88                JC     RET
030E 3C 0A                CMP     AL,10

```

0310 F5	CMC	
0311 73 83	JNC	RET ;OK if 0-9
0313 2C 07	SUB	AL,7 ;Kill A-F bias
0315 3C 0A	CMP	AL,10
0317 72 03	JC	RET
0319 3C 10	CMP	AL,16
031B F5	CMC	
031C C3	RET:	RET
031D		
031D		;Process one parameter when a list of bytes is
031D		;required. Carry set if parameter bad. Called by LIST
031D		
031D		LISTITEM:
031D E8 FC FD	CALL	SCANP ;Scan to parameter
0320 E8 E5 FF	CALL	HEXIN ;Is it in hex?
0323 72 0B	JC	STRINGCHK ;If not, could be a string
0325 B9 02 00	MOV	CX,2 ;Only 2 hex digits for bytes
0328 E8 BF FF	CALL	GETHEX ;Get the byte value
032B 88 17	MOV	[BX],DL ;Add to list
032D 43	INC	BX
032E F8	GRET:	CLC ;Parameter was OK
032F C3	RET	
0330		STRINGCHK:
0330 8A 05	MOV	AL,[DI] ;Get first character of param
0332 3C 27	CMP	AL,"'" ;String?
0334 74 06	JZ	STRING
0336 3C 22	CMP	AL,"'" ;Either quote is all right
0338 74 02	JZ	STRING
033A F9	STC	
033B C3	RET	;Not string, not hex - bad
033C		STRING:
033C 8A E0	MOV	AH,AL ;Save for closing quote
033E 47	INC	DI
033F		STRNGLP:
033F 8A 05	MOV	AL,[DI] ;Next char of string
0341 47	INC	DI
0342 3C 0D	CMP	AL,13 ;Check for end of line
0344 74 23	JZ	ERROR ;Must find a close quote
0346 3A C4	CMP	AL,AH ;Check for close quote
0348 75 05	JNZ	STOSTRG ;Add new character to list
034A 3A 25	CMP	AH,[DI] ;Two quotes in a row?
034C 75 E0	JNZ	GRET ;If not, we're done
034E 47	INC	DI ;Yes - skip second one
034F		STOSTRG:
034F 88 07	MOV	[BX],AL ;Put new char in list
0351 43	INC	BX
0352 EB EB	JP	STRNGLP ;Get more characters
0354		
0354		;Get a byte list for ENTER, FILL or SEARCH. Accepts any number
0354		;of 2-digit hex values or character strings in either single
0354		;(') or double ("") quotes.
0354		
0354		LIST:
0354 BB 18 01	MOV	BX,LINEBUF ;Put byte list in the line buffer
0357		LISTLP:
0357 E8 C3 FF	CALL	LISTITEM ;Process a parameter
035A 73 FB	JNC	LISTLP ;If OK, try for more
035C 81 EB 18 01	SUB	BX,LINEBUF ;BX now has no. of bytes in list
0360 74 07	JZ	ERROR ;List must not be empty
0362		
0362		;Make sure there is nothing more on the line except for
0362		;blanks and carriage return. If there is, it is an
0362		;unrecognized parameter and an error.
0362		
0362		GETEOL:
0362 E8 C0 FD	CALL	SCANB ;Skip blanks
0365 75 02	JNZ	ERROR ;Better be a RETURN
0367 C3	RET	
0368		

```

0368 ;Command error. DI has been incremented beyond the
0368 ;command letter so it must decremented for the
0368 ;error pointer to work.
0368
0368 PERR:
0368 4F DEC DI
0369
0369 ;Syntax error. DI points to character in the input buffer
0369 ;which caused error. By subtracting from start of buffer,
0369 ;we will know how far to tab over to appear directly below
0369 ;it on the terminal. Then print "^ Error".
0369
0369 ERROR:
0369 81 EF 17 01 SUB DI,LINEBUF-1 ;How many char processed so far?
036D 8B CF MOV CX,DI ;Parameter for TAB in CX
036F E8 05 FE CALL TAB ;Directly below bad char
0372 BE 6A 07 MOV SI,SYNERR ;Error message
0375
0375 ;Print error message and abort to command level
0375
0375 PRINT:
0375 E8 9A FD CALL PRINTMES
0378 E9 0C FD JMP COMMAND
037B
037B ;Short form of ENTER command. A list of values from the
037B ;command line are put into memory without using normal
037B ;ENTER mode.
037B
037B GETLIST:
037B E8 D6 FF CALL LIST ;Get the bytes to enter
037E 5F POP DI ;Displacement within segment
037F 07 POP ES ;Segment to enter into
0380 BE 18 01 MOV SI,LINEBUF ;List of bytes is in line buffer
0383 8B CB MOV CX,BX ;Count of bytes
0385 F3 REP
0386 A4 MOVB ;Enter that byte list
0387 C3 RET
0388
0388 ;Enter values into memory at a specified address. If the
0388 ;line contains nothing but the address we go into "enter
0388 ;mode", where the address and its current value are printed
0388 ;and the user may change it if desired. To change, type in
0388 ;new value in hex. Backspace works to correct errors. If
0388 ;an illegal hex digit or too many digits are typed, the
0388 ;bell is sounded but it is otherwise ignored. To go to the
0388 ;next byte (with or without change), hit space bar. To
0388 ;back up to a previous address, type "-". On
0388 ;every 8-byte boundary a new line is started and the address
0388 ;is printed. To terminate command, type carriage return.
0388 ; Alternatively, the list of bytes to be entered may be
0388 ;included on the original command line immediately following
0388 ;the address. This is in regular LIST format so any number
0388 ;of hex values or strings in quotes may be entered.
0388
0388 ENTER:
0388 B9 05 00 MOV CX,5 ;5 digits in address
038B E8 5C FF CALL GETHEX ;Get ENTER address
038E E8 12 FE CALL GETSEG ;Convert to seg/disp format
0391 ;Adjust segment and displacement so we are in the middle
0391 ;of the segment instead of the very bottom. This allows
0391 ;backing up a long way.
0391 82 EC 08 SUB AH,8 ;Adjust segment 32K down
0394 80 C6 80 ADD DH,80H ; and displacement 32K up
0397 50 PUSH AX ;Save for later
0398 52 PUSH DX
0399 E8 89 FD CALL SCANB ;Any more parameters?
039C 75 DD JNZ GETLIST ;If not end-of-line get list
039E 5F POP DI ;Displacement of ENTER
039F 07 POP ES ;Segment
03A0 GETROW:

```

03A0 E8 9A FD	CALL	OUTDI	;Print address of entry
03A3 E8 CD FD	CALL	BLANK	;Leave a space
03A6	GETBYTE:		
03A6 26	SEG	ES	
03A7 8A 05	MOV	AL,[DI]	;Get current value
03A9 E8 A7 FD	CALL	HEX	;And display it
03AC B0 2E	MOV	AL,"."	
03AE E8 B7 FD	CALL	OUT	;Prompt for new value
03B1 B9 02 00	MOV	CX,2	;Max of 2 digits in new value
03B4 BA 00 00	MOV	DX,0	;Initial new value
03B7	GETDIG:		
03B7 E8 48 FD	CALL	IN	;Get digit from user
03BA 8A E0	MOV	AH,AL	;Save
03BC E8 4B FF	CALL	HEXCHK	;Hex digit?
03BF 86 E0	XCHG	AH,AL	;Need original for echo
03C1 72 0C	JC	NOHEX	;If not, try special command
03C3 E8 A2 FD	CALL	OUT	;Echo to console
03C6 8A F2	MOV	DH,DL	;Rotate new value
03C8 8A D4	MOV	DL,AH	;And include new digit
03CA E2 EB	LOOP	GETDIG	;At most 2 digits
03CC	;We have two digits, so all we will accept now is a command.		
03CC	WAIT:		
03CC E8 33 FD	CALL	IN	;Get command character
03CF	NOHEX:		
03CF 3C 08	CMP	AL,8	;Backspace
03D1 74 19	JZ	BS	
03D3 3C 7F	CMP	AL,7FH	;RUBOUT
03D5 74 15	JZ	BS	
03D7 3C 2D	CMP	AL,"_"	;Back up to previous address
03D9 74 4D	JZ	PREV	
03DB 3C 0D	CMP	AL,13	;All done with command?
03DD 74 2F	JZ	EOL	
03DF 3C 20	CMP	AL," "	;Go to next address
03E1 74 31	JZ	NEXT	
03E3	;If we got here, character was invalid. Sound bell.		
03E3 B0 07	MOV	AL,7	
03E5 E8 80 FD	CALL	OUT	
03E8 E3 E2	JCXZ	WAIT	;CX=0 means no more digits
03EA EB CB	JP	GETDIG	;Don't have 2 digits yet
03EC	BS:		
03EC 82 F9 02	CMP	CL,2	;CX=2 means nothing typed yet
03EF 74 C6	JZ	GETDIG	;Can't back up over nothing
03F1 FE C1	INC	CL	;Accept one more character
03F3 8A D6	MOV	DL,DH	;Rotate out last digit
03F5 8A F5	MOV	DH,CH	;Zero this digit
03F7 E8 15 FD	CALL	BACKUP	;Physical backspace
03FA EB BB	JP	GETDIG	;Get more digits
03FC	;If new value has been entered, convert it to binary and		
03FC	;put into memory. Always bump pointer to next location		
03FC	STORE:		
03FC 82 F9 02	CMP	CL,2	;CX=2 means nothing typed yet
03FF 74 0B	JZ	NOSTO	;So no new value to store
0401	;Rotate DH left 4 bits to combine with DL and make a byte value		
0401 51	PUSH	CX	
0402 B1 04	MOV	CL,4	
0404 D2 E6	SHL	DH,CL	
0406 59	POP	CX	
0407 0A D6	OR	DL,DH	;Hex is now converted to binary
0409 26	SEG	ES	
040A 88 15	MOV	[DI],DL	;Store new value
040C	NOSTO:		
040C 47	INC	DI	;Prepare for next location
040D C3	RET		
040E	EOL:		
040E E8 EB FF	CALL	STORE	;Enter the new value
0411 E9 E0 FC	JMP	CRLF	;CR/LF and terminate
0414	NEXT:		
0414 E8 E5 FF	CALL	STORE	;Enter new value

0417 41	INC	CX	;Leave a space plus two for
0418 41	INC	CX	; each digit not entered
0419 E8 5B FD	CALL	TAB	
041C 8B C7	MOV	AX,DI	;Next memory address
041E 24 07	AND	AL,7	;Check for 8-byte boundary
0420 75 84	JNZ	GETBYTE	;Take 8 per line
0422	NEWROW:		
0422 E8 CF FC	CALL	CRLF	;Terminate line
0425 E9 78 FF	JMP	GETROW	;Print address on new line
0428	PREV:		
0428 E8 D1 FF	CALL	STORE	;Enter the new value
042B	;DI has been bumped to next byte. Drop it 2 to go to previous addr		
042B 4F	DEC	DI	
042C 4F	DEC	DI	
042D EB F3	JP	NEWROW	;Terminate line after backing up
042F			
042F	;Perform register dump if no parameters or set register if a		
042F	;register designation is a parameter.		
042F	REG:		
042F E8 EA FC	CALL	SCANP	
0432 74 62	JZ	DISPREG	
0434 8A 15	MOV	DL,[DI]	
0436 47	INC	DI	
0437 8A 35	MOV	DH,[DI]	
0439 82 FE OD	CMP	DH,13	
043C 74 76	JZ	FLAG	
043E 47	INC	DI	
043F E8 20 FF	CALL	GETEOL	
0442 82 FE 20	CMP	DH," "	
0445 74 6D	JZ	FLAG	
0447 BF D7 06	MOV	DI,REGTAB	
044A 92	XCHG	AX,DX	
044B 0E	PUSH	CS	
044C 07	POP	ES	
044D B9 0E 00	MOV	CX,REGTABLEN	
0450 F2	REPNZ		
0451 AF	SCAW		
0452 75 3C	JNZ	BADREG	
0454 0B C9	OR	CX,CX	
0456 75 06	JNZ	NOTPC	
0458 4F	DEC	DI	
0459 4F	DEC	DI	
045A 2E	SEG	CS	
045B 8B 45 FE	MOV	AX,[DI-2]	
045E	NOTPC:		
045E E8 07 FD	CALL	OUT	
0461 8A C4	MOV	AL,AH	
0463 E8 02 FD	CALL	OUT	
0466 E8 0A FD	CALL	BLANK	
0469 1E	PUSH	DS	
046A 07	POP	ES	
046B 8D 9D C3 FA	LEA	BX,[DI+REGDIF-2]	
046F 8B 17	MOV	DX,[BX]	
0471 E8 D8 FC	CALL	OUT16	
0474 E8 7D FC	CALL	CRLF	
0477 B0 3A	MOV	AL,":"	
0479 E8 EC FC	CALL	OUT	
047C E8 42 FC	CALL	INBUF	
047F E8 A3 FC	CALL	SCANB	
0482 74 0B	JZ	RET3	
0484 B9 04 00	MOV	CX,4	
0487 E8 63 FE	CALL	GETHEX1	
048A E8 D5 FE	CALL	GETEOL	
048D 89 17	MOV	[BX],DX	
048F C3	RET3:	RET	
0490	BADREG:		
0490 B8 42 52	MOV	AX,5200H+"B"	;BR ERROR
0493 E9 96 00	JMP	ERR	
0496	DISPREG:		

0496 BE D7 06	MOV	SI,REGTAB
0499 BB 9C 01	MOV	BX,AXSAVE
049C B9 08 00	MOV	CX,8
049F E8 65 00	CALL	DISPREGLINE
04A2 E8 4F FC	CALL	CRLF
04A5 B9 05 00	MOV	CX,5
04A8 E8 5C 00	CALL	DISPREGLINE
04AB E8 C5 FC	CALL	BLANK
04AE E8 93 00	CALL	DISPFLAGS
04B1 E9 40 FC	JMP	CRLF
04B4	FLAG:	
04B4 82 FA 46	CMP	DL,"F"
04B7 75 D7	JNZ	BADREG
04B9 E8 88 00	CALL	DISPFLAGS
04BC B0 2D	MOV	AL,"_"
04BE E8 A7 FC	CALL	OUT
04C1 E8 FD FB	CALL	INBUF
04C4 E8 5E FC	CALL	SCANB
04C7 33 DB	XOR	BX,BX
04C9 8B 16 B6 01	MOV	DX,[FSAVE]
04CD	GETFLG:	
04CD 8B F7	MOV	SI,DI
04CF AD	LODW	
04D0 3C 0D	CMP	AL,13
04D2 74 66	JZ	SAVCHG
04D4 82 FC 0D	CMP	AH,13
04D7 74 66	JZ	FLGERR
04D9 BF F3 06	MOV	DI,FLAGTAB
04DC B9 20 00	MOV	CX,32
04DF 0E	PUSH	CS
04E0 07	POP	ES
04E1 F2	REPNE	
04E2 AF	SCAW	
04E3 75 5A	JNZ	FLGERR
04E5 8A E9	MOV	CH,CL
04E7 80 E1 0F	AND	CL,OFH
04EA B8 01 00	MOV	AX,1
04ED D3 C0	ROL	AX,CL
04EF 85 C3	TEST	AX,BX
04F1 75 33	JNZ	REPFLG
04F3 0B D8	OR	BX,AX
04F5 0B D0	OR	DX,AX
04F7 F6 C5 10	TEST	CH,16
04FA 75 02	JNZ	NEXFLG
04FC 33 D0	XOR	DX,AX
04FE	NEXFLG:	
04FE 8B FE	MOV	DI,SI
0500 1E	PUSH	DS
0501 07	POP	ES
0502 E8 17 FC	CALL	SCANP
0505 EB C6	JP	GETFLG
0507	DISPREGLINE:	
0507 2E	SEG	CS
0508 AD	LODW	
0509 E8 5C FC	CALL	OUT
050C 8A C4	MOV	AL,AH
050E E8 57 FC	CALL	OUT
0511 B0 3D	MOV	AL,"="
0513 E8 52 FC	CALL	OUT
0516 8B 17	MOV	DX,[BX]
0518 43	INC	BX
0519 43	INC	BX
051A E8 2F FC	CALL	OUT16
051D E8 53 FC	CALL	BLANK
0520 E8 50 FC	CALL	BLANK
0523 E2 E2	LOOP	DISPREGLINE
0525 C3	RET	
0526	REPFLG:	
0526 B8 44 46	MOV	AX,4600H+"D" ;DF ERROR
0529	FERR:	

0529 E8 0E 00		CALL	SAVCHG
052C	ERR:		
052C E8 39 FC		CALL	OUT
052F 8A C4		MOV	AL,AH
0531 E8 34 FC		CALL	OUT
0534 BE 6B 07		MOV	SI,ERRMES
0537 E9 3B FE		JMP	PRINT
053A	SAVCHG:		
053A 89 16 B6 01		MOV	[FSAVE],DX
053E C3		RET	
053F	FLGERR:		
053F B8 42 46		MOV	AX,4600H+"B" ;BF ERROR
0542 EB E5		JP	FERR
0544	DISPFLAGS:		
0544 BE F3 06		MOV	SI,FLAGTAB
0547 B9 10 00		MOV	CX,16
054A 8B 16 B6 01		MOV	DX,[FSAVE]
054E	DFLAGS:		
054E 2E		SEG	CS
054F AD		LODW	
0550 D1 E2		SHL	DX
0552 72 04		JC	FLAGSET
0554 2E		SEG	CS
0555 8B 44 1E		MOV	AX,[SI+30]
0558	FLAGSET:		
0558 0B C0		OR	AX,AX
055A 74 0B		JZ	NEXTFLG
055C E8 09 FC		CALL	OUT
055F 8A C4		MOV	AL,AH
0561 E8 04 FC		CALL	OUT
0564 E8 OC FC		CALL	BLANK
0567	NEXTFLG:		
0567 E2 E5		LOOP	DFLAGS
0569 C3		RET	
056A			
056A	TRACE:		
056A E8 AF FB		CALL	SCANP
056D E8 98 FD		CALL	HEXIN
0570 BA 01 00		MOV	DX,1
0573 72 06		JC	STOCNT
0575 B9 04 00		MOV	CX,4
0578 E8 6F FD		CALL	GETHEX
057B	STOCNT:		
057B 89 16 02 01		MOV	[TCOUNT],DX
057F E8 E0 FD		CALL	GETEOL
0582	STEP:		
0582 C7 06 00 01 00 00		MOV	[BRKCNT],0
0588 80 OE B7 01 01		OR	B,[FSAVE+1],1
058D	EXIT:		
058D C7 06 0C 00 D1 05		MOV	[12],BREAKFIX
0593 8C 0E 0E 00		MOV	[14],CS
0597 C7 06 04 00 D8 05		MOV	[4],REENTER
059D 8C 0E 06 00		MOV	[6],CS
05A1 FA		DI	
05A2 C7 06 64 00 D8 05		MOV	[64H],REENTER
05A8 8C 0E 66 00		MOV	[66H],CS
05AC BC 9C 01		MOV	SP,STACK
05AF 58		POP	AX
05B0 5B		POP	BX
05B1 59		POP	CX
05B2 5A		POP	DX
05B3 5D		POP	BP
05B4 5D		POP	BP
05B5 5E		POP	SI
05B6 5F		POP	DI
05B7 07		POP	ES

05B8 07	POP	ES
05B9 17	POP	SS
05BA 8B 26 A4 01	MOV	[SPSAVE]
05BE FF 36 B6 01	PUSH	[FSAVE]
05C2 FF 36 B2 01	PUSH	[CSSAVE]
05C6 FF 36 B4 01	PUSH	[IPSAVE]
05CA 8E 1E AC 01	MOV	DS,[DSSAVE]
05CE CF	IRET	
05CF EB B1	STEP1:	JP STEP
05D1		
05D1	;Re-entry point from breakpoint. Need to decrement instruction	
05D1	;pointer so it points to location where breakpoint actually	
05D1	;occured.	
05D1	BREAKFIX:	
05D1 87 EC	XCHG	SP,BP
05D3 FF 4E 00	DEC	[BP]
05D6 87 EC	XCHG	SP,BP
05D8		
05D8	;Re-entry point from trace mode or interrupt during	
05D8	;execution. All registers are saved so they can be	
05D8	;displayed or modified.	
05D8	REENTER:	
05D8 2E	SEG	CS
05D9 89 26 A4 09	MOV	[SPSAVE+SEGDIF],SP
05DD 2E	SEG	CS
05DE 8C 16 B0 09	MOV	[SSSAVE+SEGDIF],SS
05E2 33 E4	XOR	SP,SP
05E4 8E D4	MOV	SS,SP
05E6 BC B0 01	MOV	SP,RSTACK
05E9 06	PUSH	ES
05EA 1E	PUSH	DS
05EB 57	PUSH	DI
05EC 56	PUSH	SI
05ED 55	PUSH	BP
05EE 4C	DEC	SP
05EF 4C	DEC	SP
05F0 52	PUSH	DX
05F1 51	PUSH	CX
05F2 53	PUSH	BX
05F3 50	PUSH	AX
05F4 16	PUSH	SS
05F5 1F	POP	DS
05F6 8B 26 A4 01	MOV	SP,[SPSAVE]
05FA 8E 16 B0 01	MOV	SS,[SSSAVE]
05FE 8F 06 B4 01	POP	[IPSAVE]
0602 8F 06 B2 01	POP	[CSSAVE]
0606 58	POP	AX
0607 80 E4 FE	AND	AH,OFEH
060A A3 B6 01	MOV	[FSAVE],AX
060D 89 26 A4 01	MOV	[SPSAVE],SP
0611 1E	PUSH	DS
0612 07	POP	ES
0613 1E	PUSH	DS
0614 17	POP	SS
0615 BC 9C 01	MOV	SP,STACK
0618 C7 06 64 00 BB 06	MOV	[64H],INT
061E B0 20	MOV	AL,20H
0620 E6 F2	OUT	BASE+2
0622 FB	EI	
0623 FC	UP	
0624 E8 CD FA	CALL	CRLF
0627 E8 6C FE	CALL	DISPREG
062A FF 0E 02 01	DEC	[TCOUNT]
062E 75 9F	JNZ	STEP1
0630		
0630 BE 04 01	MOV	SI,BPTAB
0633 8B 0E 00 01	MOV	CX,[BRKCNT]
0637 E3 10	JCXZ	COMJMP

```

0639      CLEARBP:
0639 8B 54 14    MOV     DX,[SI+BPLEN]
063C AD          LODW    AX
063D 50          PUSH    GETSEG
063E E8 62 FB    CALL    ES,AX
0641 8E C0          MOV    DI,DX
0643 8B FA          POP    AX
0645 58          STOB    CLEARBP
0646 AA          LOOP    COMMAND
0647 E2 F0          COMJMP: JMP   COMMAND

064C          ;Input from the specified port and display result
064C
064C          INPUT:
064C B9 04 00    MOV     CX,4      ;Port may have 4 digits
064F E8 98 FC    CALL    GETHEX   ;Get port number in DX
0652 EC          INB     DX        ;Variable port input
0653 E8 FD FA    CALL    HEX      ;And display
0656 E9 9B FA    JMP     CRLF

0659          ;Output a value to specified port.
0659
0659          OUTPUT:
0659 B9 04 00    MOV     CX,4      ;Port may have 4 digits
065C E8 8B FC    CALL    GETHEX   ;Get port number
065F 52          PUSH    DX        ;Save while we get data
0660 B9 02 00    MOV     CX,2      ;Byte output only
0663 E8 84 FC    CALL    GETHEX   ;Get data to output
0666 92          XCHG    AX,DX    ;Output data in AL
0667 5A          POP     DX        ;Port in DX
0668 EE          OUTB    DX        ;Variable port output
0669 C3          RET

066A          ;Jump to program, setting up registers according to the
066A          ;save area. Up to 10 breakpoint addresses may be specified.
066A
066A          GO:
066A BB 18 01    MOV     BX,LINEBUF
066D 33 F6    XOR     SI,SI
066F          GO1:
066F E8 AA FA    CALL    SCANP
0672 74 19    JZ      EXEC
0674 B9 05 00    MOV     CX,5
0677 E8 70 FC    CALL    GETHEX
067A 89 17    MOV     [BX],DX
067C 88 67 ED    MOV     [BX-BPLEN+1],AH
067F 43          INC     BX
0680 43          INC     BX
0681 46          INC     SI
0682 83 FE 0B    CMP     SI,BPMAX+1
0685 75 E8    JNZ    GO1
0687 B8 42 50    MOV     AX,5000H+"B"  ;BP ERROR
068A E9 9F FE    JMP     ERR
068D          EXEC:
068D 89 36 00 01    MOV     [BRKCNT],SI
0691 E8 CE FC    CALL    GETEOL
0694 8B CE    MOV     CX,SI
0696 E3 1A    JCXZ   NOBP
0698 BE 04 01    MOV     SI,BPTAB
069B          SETBP:
069B 8B 54 14    MOV     DX,[SI+BPLEN]
069E AD          LODW    GETSEG
069F E8 01 FB    CALL    DS,AX
06A2 8E D8    MOV     DI,DX
06A4 8B FA    MOV     AL,[DI]
06A6 8A 05    MOV     B,[DI],OCCH
06A8 C6 05 CC    PUSH    ES
06AB 06          POP    DS
06AC 1F

```

06AD 88 44 FE	MOV [SI-2],AL	
06B0 E2 E9	LOOP SETBP	
06B2	NOBP:	
06B2 C7 06 02 01 01 00	MOV [TCOUNT],1	
06B8 E9 D2 FE	JMP EXIT	
06BB	;Console input interrupt handler. Used to interrupt commands	
06BB	;or programs under execution (if they have interrupts	
06BB	;enabled). Control-S causes a loop which waits for any other	
06BB	;character to be typed. Control-C causes abort to command	
06BB	;mode. All other characters are ignored.	
06BB	INT:	
06BB 50	PUSH AX ;Don't destroy accumulator	
06BC	;Output End-of-Interrupt commands to slave 8259A. This	
06BC	;wouldn't be necessary if Automatic End of Interrupt mode	
06BC	;worked like it was supposed to!	
06BC B0 20	MOV AL,20H	
06BE E6 F2	OUT BASE+2	
06C0 E4 F6	IN DATA ;Get interrupting character	
06C2 24 7F	AND AL,7FH ;ASCII has only 7 bits	
06C4 3C 13	CMP AL,"S"-@" ;Check for Control-S	
06C6 75 03	JNZ NOSTOP	
06C8 E8 37 FA	CALL IN ;Wait for continue character	
06CB	NOSTOP:	
06CB 3C 03	CMP AL,"C"-@" ;Check for Control-C	
06CD 74 02	JZ BREAK	
06CF	;Just ignore interrupt - restore AX and return	
06CF 58	POP AX	
06D0 CF	IRET	
06D1	BREAK:	
06D1 E8 20 FA	CALL CRLF	
06D4 E9 B0 F9	JMP COMMAND	
06D7	REGTAB:	
06D7 41 58 42 58 43 58	DB "AXBXCDXSPBPSIDIDSESSSCSIPPC"	
44 58 53 50 42 50		
53 49 44 49 44 53		
45 53 53 53 43 53		
49 50 50 43		
06F3	REGDIF: EQU AXSAVE-REGTAB	
06F3	;Flags are ordered to correspond with the bits of the flag	
06F3	;register, most significant bit first, zero if bit is not	
06F3	;a flag. First 16 entries are for bit set, second 16 for	
06F3	;bit reset.	
06F3	FLAGTAB:	
06F3 00 00	DW 0	
06F5 00 00	DW 0	
06F7 00 00	DW 0	
06F9 00 00	DW 0	
06FB 4F 56	DB "OV"	
06FD 44 4E	DB "DN"	
06FF 45 49	DB "EI"	
0701 00 00	DW 0	
0703 4E 47	DB "NG"	
0705 5A 52	DB "ZR"	
0707 00 00	DW 0	
0709 41 43	DB "AC"	
070B 00 00	DW 0	
070D 50 45	DB "PE"	
070F 00 00	DW 0	
0711 43 59	DB "CY"	
0713 00 00	DW 0	
0715 00 00	DW 0	
0717 00 00	DW 0	
0719 00 00	DW 0	
071B 4E 56	DB "NV"	
071D 55 50	DB "UP"	
071F 44 49	DB "DI"	

0721 00 00	DW	0
0723 50 4C	DB	"PL"
0725 4E 5A	DB	"NZ"
0727 00 00	DW	0
0729 4E 41	DB	"NA"
072B 00 00	DW	0
072D 50 4F	DB	"PO"
072F 00 00	DW	0
0731 4E 43	DB	"NC"
0733		
0733	;Initialization table. First byte of each entry is no.	
0733	;of bytes to output to the corresponding port. That	
0733	;many initialization bytes follow.	
0733		
0733	INITTABLE:	
0733	;Port BASE+0 - Master 8259A. Initialization Command Word (ICW)	
0733	;One sets level-triggered mode, multiple 8259As, require	
0733	;ICW4.	
0733 01	DB	1
0734 19	DB	19H
0735	;Port BASE+1 - Master 8259A. ICW2 sets vector base to 10H	
0735	;ICW3 sets a slave on interrupt input 1; ICW4 sets buffered	
0735	;mode, as a master, with Automatic End of Interrupt, 8086	
0735	;vector; Operation Command Word (OCW) One sets interrupt	
0735	;mask to enable line 1 (slave 8259A) only.	
0735 04	DB	4
0736 10 02 0F FD	DB	10H,2,0FH,0FDH
073A	;Port BASE+2 - Slave 8259A. ICW1 sets level-triggered mode,	
073A	;multiple 8259As, require ICW4.	
073A 01	DB	1
073B 19	DB	19H
073C	;Port BASE+3 - Slave 8259A. ICW2 sets vector base to 18H	
073C	;ICW3 sets slave address as 1; ICW4 sets buffered mode,	
073C	;as slave, with Automatic End of Interrupt (which doesn't	
073C	;work in slaves), 8086 vector; OCW1 sets interrupt mask	
073C	;to enable line 1 (serial receive) only.	
073C 04	DB	4
073D 18 01 0B FD	DB	18H,1,0BH,0FDH
0741	;Port Base+4 - 9513 Data. 9513 has previously been set	
0741	;up for Counter 5 mode register with auto increment. Thus	
0741	;mode is set to 0B63H, which is no gating, count source is	
0741	;F1 (4 MHz), reload from load or hold, count down repetitively	
0741	;in binary, with output toggle. Load register is set to	
0741	;0007H, and Hold register is set to 0006H. Thus we	
0741	;alternately divide by 7 and 6, which is divided by 2 by	
0741	;the output toggle, thus providing a square wave of	
0741	;4 MHz/13 = 307.7 kHz, which divided by 16 in the 8251A	
0741	;provides 19,230 baud (0.16% high).	
0741 06	DB	6
0742 63 0B 07 00 06 00	DB	63H,0BH,7,0,6,0
0748	;Port BASE+5 - 9513 Control. Load and arm counter 5,	
0748	;enabling baud rate generation. Then select counter	
0748	;5 mode register, in case baud rate wasn't right.	
0748 02	DB	2
0749 70 05	DB	70H,5
074B	;Port BASE+6 - 8251A Data. No initialization to this port.	
074B 00	DB	0
074C	;Port BASE+7 - 8251A Control. Since it is not possible to	
074C	;know whether the 8251A next expects a Mode Instruction or	
074C	;a Command Instruction, a dummy byte is sent which could	
074C	;safely be interpreted as either but guarantees it is now	
074C	;expecting a Command. The command sent is Internal Reset	
074C	;which causes it to start expecting a mode. The mode sent	
074C	;is for 2 stop bits, no parity, 8 data bits, 16X clock.	
074C	;This is followed by the command to error reset, enable	
074C	;transmitter and receiver, set RTS and DTR to +12V.	
074C 04	DB	4
074D B7 77 CE 37	DB	0B7H,77H,0CEH,37H
0751 0D 0A 0A 53 43 50	HEADER: DM	13,10,10,"SCP 8086 Monitor 1.5",13,10
20 38 30 38 36 20		

```

4D 6F 6E 69 74 6F
72 20 31 2E 35 OD
8A
076A 5E           SYNERR: DB      ^~^
076B 20 45 72 72 6F 72  ERRMES: DM      " Error",13,10
          OD 8A
0773 08 20 88     BACMES: DM      8,32,8
0776
0776 ;Disk boot. Select one of the following routines by
0776 ;setting the equates at the start of this program.
0776
0776 BOOT:
0776 57           PUSH    DI
0777
0777 ;*****
0777
0777 ;Boot for Cromemco 4FDC disk controller with either
0777 ;large or small disks. Loads track 0, sector 1 into LOAD.
0777
0777 IF      CROMEMCO4FDC
0777
0777 DISK: EQU   30H
0777
0777 0777 B0 01           MOV    AL,1
0779 E6 02           OUT    2           ;Reset 4FDC serial I/O
077B B0 84           MOV    AL,84H
077D E6 00           OUT    0           ;and set for 300 baud
077F B0 7F           MOV    AL,7FH
0781 E6 04           OUT    4
0783 B2 21           MOV    DL,21H
0785
0785 B0 D0           RETRY:
0787 E6 30           MOV    AL,ODOH
0789
0789 E4 30           OUTB   DISK
078B D0 C8
078D 72 FA
078F 80 F2 10
0792 8A C2
0794 E6 34
0796 BF 00 02
0799 B0 OC
079B E6 30
079D
079D E4 34           HOME:
079F D0 C8
07A1 73 FA
07A3 E4 30
07A5 24 98
07A7 75 DC
07A9 B0 01
07AB E6 32
07AD B9 80 00
07B0 8A C2
07B2 OC 80
07B4 E6 34
07B6 B0 8C
07B8 E6 30
07BA
07BA E4 34           READ:
07BC D0 C8
07BE 72 0B
07C0 E4 33
07C2 AA
07C3 E2 F5
07C5
07C5 E4 34           WSTAT:
07C7 D0 C8
07C9 73 FA           INB    DISK+4
                      ROR    AL
                      JNC    WSTAT

```

```

07CB          DONE:
07CB E4 30      INB    DISK
07CD 24 9C      AND    AL,9CH
07CF 75 B4      JNZ    RETRY
07D1          ENDIF
07D1
07D1          POP    DS
07D1          ENDIF
07D1 ;Successful read
07D1 C7 06 B2 01 00 00  MOV    [CSSAVE],0
07D7 C7 06 B4 01 00 02  MOV    [IPSAVE],LOAD
07DD 5F          POP    DI
07DE E9 89 FE      JMP    GO
07E1

Error Count = 0

0777          ****
0777
0777 ;Boot for North Star disk, single density.
0777 ;Loads track 0, sector 0 into address LOAD
0777 ;Bug in North Star boot fixed 5-26-81.
0777
0777          IF     NORTHSTARSD
0777
0777 ;Disk command equates
0777
0777          SEL:   EQU    1
0777          STP1:  EQU    9
0777          STP2:  EQU    8
0777          NOP:   EQU    10H
0777          SEC:   EQU    14H
0777          STPOUT: EQU    1CH
0777          RD:    EQU    40H
0777          BST:   EQU    20H
0777
0777 1E          PUSH   DS
0778 B8 B8 FE      MOV    AX,0FEB8H
077B 8E D8          MOV    DS,AX
077D A0 01 00      MOV    AL,[SEL]
0780 B9 14 00      MOV    CX,20
0783          MOTOR:
0783 E8 19 00      CALL   SECTOR
0786 E2 FB          LOOP   MOTOR
0788          CHKTRK:
0788 F6 06 1C 00.01  TEST   B,[STPOUT],1
078D 75 1B          JNZ    ONTRACK
078F A0 09 00      MOV    AL,[STP1]
0792 D4 OA          AAM
0794 A0 08 00      MOV    AL,[STP2]
0797 E8 05 00      CALL   SECTOR
079A E8 02 00      CALL   SECTOR
079D EB E9          JP     CHKTRK
079F          SECTOR:
079F A0 14 00      MOV    AL,[SEC] ; Reset sector flag.
07A2          SECLP:
07A2 F6 06 10 00 80  TEST   B,[NOP],80H ; Wait for sector flag.
07A7 74 F9          JZ     SECLP
07A9 C3          RET
07AA          ONTRACK:
07AA BF 00 02      MOV    DI,LOAD
07AD B9 18 01      MOV    CX,280
07B0 BB 50 00      MOV    BX,RD+NOP
07B3          GETSEC:
07B3 E8 E9 FF      CALL   SECTOR
07B6 F6 06 30 00 OF  TEST   B,[BST+NOP],0FH ; Test for sector zero.
07BB 75 F6          JNZ    GETSEC
07BD          GETSYNC:
07BD F6 06 10 00 04  TEST   B,[NOP],4
07C2 E1 F9          LOOPZ  GETSYNC

```

07C4 74 E4	JZ	ONTRACK
07C6 B9 00 01	MOV	CX,100H
07C9 32 D2	XOR	DL,DL
07CB D5 OA	AAD	
07CD	READ:	
07CD 8A 07	MOV	AL,[BX]
07CF AA	STOB	
07D0 32 D0	XOR	DL,AL
07D2 D0 C2	ROL	DL
07D4 D5 OA	AAD	
07D6 E2 F5	LOOP	READ
07D8 8A 07	MOV	AL,[BX]
07DA 3A C2	CMP	AL,DL
07DC 75 CC	JNZ	ONTRACK
07DE 1F	POP	DS
07DF	ENDIF	
07DF	;Successful read	
07DF C7 06 B2 01 00 00	MOV	[CSSAVE],0
07E5 C7 06 B4 01 00 02	MOV	[IPSAVE],LOAD
07EB 5F	POP	DI
07EC E9 7B FE	JMP	GO
07EF		

Error Count = 0

0777	*****	
0777		
0777	;Boot for Tarbell disk controllers. Load track 0,	
0777	;sector 1 into LOAD.	
0777	IF	TARBELL
0777	DISK:	EQU 78H
0777	DCOM:	JP RETRY
0777 EB 09		OUTB DISK
0779 E6 78		MOV AL,50
077B B0 32	HOLD:	
077D		DEC AL
077D FE C8		JNZ HOLD
077F 75 FC		RET
0781 C3	RETRY:	
0782		MOV AL,ODOH
0782 B0 D0		CALL DCOM
0784 E8 F2 FF	READY:	
0787		INB DISK
0787 E4 78		ROR AL
0789 D0 C8		JC READY
078B 72 FA		MOV DI,LOAD
078D BF 00 02		MOV AL,0EH ;Home command @ 10ms/track
0790 B0 OE		CALL DCOM
0792 E8 E4 FF		INB DISK+4
0795 E4 7C		INB DISK
0797 E4 78		AND AL,98H
0799 24 98		JNZ RETRY
079B 75 E5		MOV AL,1
079D B0 01		OUTB DISK+2
079F E6 7A		MOV CX,80H
07A1 B9 80 00		MOV AL,8CH
07A4 B0 8C		CALL DCOM
07A6 E8 D0 FF	READ:	
07A9		INB DISK+4
07A9 E4 7C		ROL AL
07AB D0 C0		JNC DONE
07AD 73 0B		INB DISK+3
07AF E4 7B		STOB READ
07B1 AA		
07B2 E2 F5		

07B4 WSTAT:
07B4 E4 7C INB DISK+4
07B6 D0 C0 ROL AL
07B8 72 FA JC WSTAT
07BA DONE:
07BA E4 78 INB DISK
07BC 24 9C AND AL,9CH
07BE 75 C2 JNZ RETRY
07C0 ;Successful read
07C0 C7 06 B2 01 00 00 MOV [CSSAVE],0
07C6 C7 06 B4 01 00 02 MOV [IPSAVE],LOAD
07CC 5F POP DI
07CD E9 9A FE JMP GO
07D0

Error Count = 0

0777 ;*****
0777
0777 IF OTHER
0777
0777 ;User may insert customized disk boot here. All
0777 ;registers are available, stack pointer is valid
0777 ;and interrupts are enabled. Stqck should be at
0777 ;same level on fall-through to code below. Last
0777 ;address available is 07DF hex.
0777
07E0 ORG 7EOH ;Simulate boot of maximum length
07E0
07E0 ENDIF
07E0
07E0 ;*****
07E0 ;Successful read
07E0 C7 06 B2 01 00 00 MOV [CSSAVE],0
07E6 C7 06 B4 01 00 02 MOV [IPSAVE],LOAD
07EC 5F POP DI
07ED E9 7A FE JMP GO
07F0

Error Count = 0



